

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 440500

Quarter corner common to Sections 10 and 15, Township 36 South, Range 4 West, W.M.

From the following evidence, at the location described below, set a 1x36 ins. galvanized iron pipe 30 ins. in the ground. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W
10
¼S —
15
C.S.
1988

Bearing tree reported as original on Survey No. 4569 found:

- Center of Maple sprouts bears Record: N8°W, 21.0 feet.

Bearing trees marked on said survey found:

- Madrone, now 8 ins. diam. with partial scribe marks visible bears S36°E, 14.1 feet to center at lower blaze. Record: S35°25'20"E, 13.68 feet apparently to lower face.
- Madrone, now 8 ins. diam. with double healed blazes, brs. Record: N51°W, 19.3 feet to center at root crown. Record distance; 18.81 feet to upper face.

The center of a north-south dry branch bears West 14 feet.

No trace could be found of the 1½ ins. diam. iron pipe reported set on Survey No. 4569.

A location poster placed on an 8 ins. Madrone bears East 100 feet and lies on the west side of a dirt road.

Corner lies on a steep west slope about 200 feet South of a switchback in a dirt road across a north-south draw.

June 8, 1988
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 17°
P. -236