

## FIRST RE-ESTABLISHMENT

GCDB 500140

Quarter corner to Sections 34 and 35, Township 36 South, Range 4 West.

Found original BTs both dead trees.

Set 3"x3"x30" post for corner from which

- a 16" Black Oak bears South 70° West, 36.9 feet.
- Scribed CS-BT a 16" White Oak bears South 82° East, 31.0 feet.

November 18, 1927  
Boyden, Deputy County Surveyor  
R. Smith, and R. Kent, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 500140

Quarter corner common to Section 34 and 35, Township 36 South, Range 4 West, W.M.

Found projecting 8 ins. the 1 ins. diam. iron pipe reported set on Survey No. 2955, in 1965.

In the top of said pipe set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W  
¼s  
34 | 35  
C.S.  
1986

Bearing tree marked on first re-establishment, page 3, in 1927 found:

- White Oak snag, now 18 ins. diam. with scribing visible in both faces brs. Record: S82°E, 31.0 feet to lower face (slope distance).

Bearing trees marked on Survey No. 2955 found

- White Oak, now 12 ins. diam. with single healed blaze, brs. N77¾°E, 46.70 feet to center of tree at root crown. Record: N76°E, 47.52 feet.
- Stump hole of White Oak, found lying alongside with scribing visible, brs. Record: N14°W, 25.74 feet to estimated position of face.

Scribe a new tree "CS" "BT":

- White Oak, 12 ins. diam., brs. S24¼°W, 67.89 feet to center of tree at lower blaze.

Corner lies in a small opening on a West slope, on the East edge of an old ditch, course North-South, and an estimated 1000 feet southeasterly from a residence at 1235 Birdseye Cr. Road.

November 26, 1986  
D. Edwards  
R. Romio

Edward McGinty  
County Surveyor

V = 21°  
P. -337