

## FIRST RE-ESTABLISHMENT

GCDB 500240

Quarter corner to Sections 26 and 27, Township 36 South, Range 4 West.

Set 2"x36" G.P. for corner ½ foot below surface of the ground.

From which

- A 42" Black Oak bears South 56°45' West, 497.2 feet, scribe CS-BT.

Set 3/8"x14" bolt on sly boundary of O. and C. Ry. R/W., which bears North 335.5 feet. The center of sly head wall culvert 463A bears North 33°45' West, 661.0 feet. Va. 20°05' East.

November 22, 1927  
Boyden, Deputy County Surveyor  
R. Smith and R. M. Kent, Chainmen

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 500240

One-quarter corner common to Sections 26 and 27, Township 36 South, Range 4 West, W.M.

At the corner found an iron pipe, 2 ins. diam., 5 ins. deep, tipped over NNW, set on First re-establishment. After straightening up said pipe (36 ins. in length), found that pipe had been moved by apparent plowing and since pipe was brittle, set a galvanized iron pipe, 1 in. in diam., 36 ins. long, 12 ins. below surface of ground, with 2½ ins. diam. bronze cap marked:

"JACKSON COUNTY 1980"  
T36S R4W  
27 | 26  
¼ Cor.

From which references as noted on First re-establishment dated 1927, page 3, are found as follows:

- Black Oak, 56 ins. diam. bears S56°40'W, 498.95 feet to center of tree, record S56°45'W, 497.2 feet.
- Iron bolt, 3/8 ins. diam., lying 0.7 feet Southerly of the Southerly right-of-way fence of the Southern Pacific Railroad, bears Record North, 335.50 feet (basis of bearing).
- Center of the Southerly concrete head wall of a culvert under the S.P. Railroad, bears N33°48'W, 660.9 feet, record N33°45'W, 661.0 feet.

New references taken:

- Scotch Pine, 8" diam., bark scribed "CS" only, bears N19°35'W, 55.0 feet to center of tree at base.
- Interstate (OSHD) 5 Highway right-of-way paddle board on metal post (77+54.15 B17 22) bears S86°02'E, 145.2 feet to centerline of post at ground.

Corner lies in undeveloped Westerly section of Valley of the Rogue State Park, approximately 57 feet South of Southerly I-5 right-of-way fence.

December 30, 1980  
R. Templin  
J. Swanson

Edward McGinty  
County Surveyor

P. 24-25

**SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT**

## THIRD RE-ESTABLISHMENT

GCDB 500240

One-quarter corner common to Sections 26 and 27, Township 36 South, Range 4 West, W.M.

At the corner found 8 ins. below surface of ground, inside of a 4 ins. diam. PVC sleeve of unknown origin, the 2½ ins. diam. bronze cap set on the Second Re-establishment, dated 1980, marked:

JACKSON COUNTY 1980  
T36S R4W  
27 | 26  
¼ Cor.

From which a bearing tree marked on the First re-establishment, dated 1927, and re-measured in 1980 found:

- Black Oak, 89 ins. diam. with healed blaze, brs. 1980 record S56°40'W, 498.95 ft. to center of tree at base. This reference is no longer visible from corner. Bearing and distance derived from an occupied reference point and used as the basis of bearing.
- Scotch Pine found dead and down. All other references noted are not intervisible and were not remeasured.

Set new references, being 5/8 x 24 ins. rebar with 2 ins. diam. aluminum caps marked "Jackson County Surveyor":

- Bears S83°09'22"W, 89.98 ft. located 2.0 ft. northeast of a 10 ins. diam. White Fir.
- Bears S24°09'56"W, 330.38 ft. located 2.0 ft. east of edge of pavement of main loop road, and 18 ft. south of camping space F34.
- Bears S04°39'28"E, 75.13 ft. located 2.5 ft. east of a 54 ins. diam. Willow.

Corner lies in Westerly section of Valley of the Rogue State Park, approximately 57 ft. South of Southerly I-5 right-of-way fence.

December 28, 2016  
B. Paull

Scott D. Fein  
Jackson County Surveyor