

FIRST RE-ESTABLISHMENT

GCDB 500600

Section corner common to Sections 2, 3, 10 and 11, Township 36 South, Range 4 West, W.M.
 $V = 20\frac{1}{4}^\circ$

Found, 2 ins. diam. G.I. pipe projecting 9 ins. as recorded on Survey No. 4569 of Jackson County Surveyor's records. Inside of which I drive a 1x36 ins. G.I. pipe projecting 12 ins. with 2½ ins. diam. bronze disc. marked:

JACKSON COUNTY 1979
T36S R4W
3 | 2
—|—
10 | 11

From which reference trees recorded on above survey bear, to unscribed upper face, as follows.

Distance measurements taken to center of tree at lower blaze.

- Black Oak, 10 ins. diam. with "BT" scribe visible in lower blaze, brs. $N81\frac{1}{2}^\circ E$, 17.94 feet.
Record: $N81^\circ 37' E$, 17.61 feet.
- Laurel, 17 ins. diam. with "BT" scribe visible in lower blaze, brs. $S15\frac{1}{4}^\circ W$, 27.4 feet.
Record: $S15^\circ 18' W$, 27.4 feet.
- Black Oak, 7 ins. diam. with "BT" scribe visible in lower blaze, brs. $N50\frac{1}{4}^\circ W$, 22.05 feet.
Record: $N50^\circ 23' W$, 22.3 feet.

I find the following original reference trees as recorded by Ives and Hyde in 1854 in Jackson County Surveyor's Records:

- Black Oak, 32 ins. diam., with open and rotted upper and lower faces, brs. $S52\frac{1}{4}^\circ W$, 63.90 feet to center of tree at lower blaze. Record: $S51^\circ W$, 63.36 feet.
- Laurel, 10 ins. diam. with old axe marks, brs. $N28\frac{1}{2}^\circ W$, 27.76 feet to center of tree at lower blaze. Record: $N28^\circ W$, 29.70 feet

I mark new reference trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Douglas Fir, 13 ins. diam. brs. $N44\frac{3}{4}^\circ E$, 8.2 feet.
- Douglas Fir, 7 ins. diam. brs. $S56\frac{1}{4}^\circ E$, 15.1 feet.

Corner lies on North slope of hill.

November 5, 1979
J. Gallegos
B. Malotte

Approved by: Edward McGinty
County Surveyor