

FIRST RE-ESTABLISHMENT

GCDB 540700

Quarter Section corner on the Township line, Section 35, Township 35 South, Range 4 West and Section 2, Township 36 South, Range 4 West.

Found original BT, a 14" Black Oak with the original scribe legible. Also a pine stump hole to the Southwest.

From which evidence,

- Set a 1"x26" galvanized iron pipe 20" in the ground for corner

From which:

- A 6" Black Oak scribed CS-BT bears S. 5°E. 27.3 feet;
- Scribe a 20" Black Oak CS-BT which bears N. 7½° E. 72.1 feet;

February 15, 1952
C. Z. Boyden
John Cox
Dean W. Pruett

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540700

Quarter corner common to Section 35, Township 35 South, Range 4 West and Section 2, Township 36 South, Range 4 West, W.M.

Found projecting 3 ins., the 1x26 ins. iron pipe reported set on first re-establishment, page 9, in 1952. Replaced with a 1x36 ins. galvanized iron pipe set 30 ins. in the ground. In the top of new pipe, set a 2½ ins. diam. brass cap marked:

T35S R4W
35
—
2
T36S
CS
1988

Original bearing tree marked by Ives and Hyde in 1854 found:

- Black Oak, now 17 ins. diam. with healed blazes bears N43°E, 24.18 feet to center of tree at root crown. Record; N41°E, 23.76 feet to face.

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of tree at lower blaze:

- Black Oak, now 20 ins. diam., brs. Record: N7½°E, 72.35 feet. Record distance; 72.1 feet.
- Black Oak, now 6 ins. diam., brs. S4°E, 27.66 feet. Record; S5°E, 27.3 feet.

Corner lies on nearly level ground, in trees and an estimated 200 feet North of a location poster nailed to a 3 ins. diam. Madrone on the Southerly side of a dirt road, course N62°E, and S62°W.

April 5, 1988
D. Edward, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

V = 18¾°
P.-125