

## FIRST RE-ESTABLISHMENT

GCDB 600300

Section corner common to Sections 23, 24, 25, 26, Township 36 South, Range 4 West, W.M.

Found original 14 ins. black oak witness tree S.7°E., 86 lks., and stump of witness tree, a B.O. S84°W., 27 lks.

From these I located corner and drove iron pin and set post beside it, marked (scribed) with the township, range and section numbers, and set new witness trees as follows:

- A black oak 14" in diam., bears S28°W, 70 feet.
- A black oak 14" in diam., bears N46½°W, 64.6 feet.
- A black oak 24" in diam., bears N64½°E, 135.6 feet.

April 29, 1913

A. T. Brown, Deputy County Surveyor

C. D. Runyon, M. B. Kellogg, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

### GCDB 600300

Section corner common to Section 23, 24, 25, and 26, Twp. 36 South, Range 4 West, W.M.  
V = 19°

Found, 2 ins. diam. iron pipe, projecting 4 ins., set by the County Engineer in 1956. Reference: Survey No. 1474, dated 1960 and North River Road Field Notes, (file A) dated 1956.

I set a 1x36 ins. G.I. pipe (inside found 2 ins. pipe) 30 ins. in the ground, with a 2½ ins. bronze disc marked:

Jackson County 1975	
T36S R4W	
23	24
26	25

From which:

- The burned stump remains of an original BT, marked by Ives and Hyde in 1854, bears record S7°E, 56.76 feet.

BTs marked by A T Brown in 1914, found as follows:

- A Black Oak, 18 ins. diam., with scribed "S" and "6" visible in exposed upper face, bears S27½°W, 70.25 feet to estimated face of lower blaze. Record, S28°W, 70.0 feet.
- A Black Oak, 19 ins. diam., scribed S23 and "Bt" in exposed faces, bears N46°W, 65.03 feet to scribed lower face. Record N46½°W, 64.6 feet.

BTs recorded on above survey (1474) found:

- A Laurel, 9 ins. diam., with scribe marks visible in partially exposed upper face, bears N43°E, 14.6 feet to center of tree at lower blaze. Record: N44½°E, 14.6 feet.
- A Laurel, 9 ins. diam., with healed blazes, bears S4½°E, 23.05 feet to center of tree at lower blaze. Record S5½°E, 22.6 feet.

**Note:** Bearings and distances to upper faces of the above two trees agree with 1960 reco Road

I marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A Black Oak, 5 ins. diam., bears S62¼°W, 51.8 feet.
- A Black Oak, 4 ins. diam., bears N77¼°W, 34.6 feet.

Corner lies on S.E. slope of hill an estimated 300 feet West of highway.

March 25, 1975

B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT**

### THIRD RE-ESTABLISHMENT

GCDB 600300

Section corner common to Sections 23, 24, 25 and 26, Township 36 South, Range 4 West, W.M.

At the corner, found projecting 4 ins., the 1 in. diam. galvanized iron pipe (inside 2 ins. diam. pipe) with 2½ ins. diam. bronze cap marked:

JACKSON COUNTY 1975	
T36S R4W	
23	24
-----	
26	25

As recorded on Second re-establishment, page 36, in 1975.

Bearing trees recorded on Second re-establishment found damaged by recent forest fire:

Marked by A T Brown in 1914:

- Black Oak, 21 ins. diam., with burned out upper face, brs. S28¼°W, 70.77 feet to center of tree. Record (1975): S27½°W, 70.25 feet to face.
- Black Oak, 21 ins. diam., containing scribe marks including "S" & "BT" in partially exposed faces, brs. N46°W, 65.16 feet to center of tree. Record (1975): 65.03 feet to face.

Marked on Survey No. 1474, dated 1960:

- Laurel, 10 ins. diam., with healed blazes brs. record (1975): N43°E, 14.6 feet to center of tree at lower blaze.
- Laurel, 10 ins. diam., with healed blazes brs. S3¾°E, 23.05 feet to center of tree at lower blaze. Record (1975): S4½°E.

Marked on Second re-establishment in 1975:

- Black Oak, 5 ins. diam., with scribing visible in partially healed blazes, brs. S62½°W, 52.06 feet to center of tree at lower blaze. Record: S62¼°W, 51.8 feet.
- Most Northerly branch, 4 ins. diam. of a double Black Oak, with scribing visible in partially healed blazes, brs. Record: N77¼°W, 34.6 feet to center of tree at lower blaze.

Mound stones around corner, set aluminum post 2 feet West of corner and new references; rebars, ⅝ ins. diam., 30 ins. long, with yellow plastic caps marked "JACKSON C.S." as follows:

- North, 45.77 feet projects 2 ins.
- South, 26.44 feet projects 4 ins.

Corner lies on steep (75%) East slope, an estimated 250 feet West of location marker on 12 ins. diam. Black Oak, located on East side on North River Road.

November 5, 1981  
E. McGinty  
R. Frost

Edward McGinty  
County Surveyor

V = 18½°  
P. -183