


**FIRST RE-ESTABLISHMENT**

**GCDB 600400**

Section corner common to Sections 13, 14, 23, and 24, Township 36 South, Range 4 West.

Found 1½" iron pipe exposed 4" for corner, drove a 1"x36" galvanized iron pipe inside said 1½" pipe with a 2½" bronze cap stamped:



From which:

- The original bearing tree (now a 16" Black Oak, with scribe) bears S3½°E, 51.6 feet to the center of the tree.
- The original bearing tree (now a 38" Laurel, left intact) bears S42½°W, 59.4 feet to the assumed upper face. (Record = S43°W, 60.7 feet)
- The original bearing tree (now an 18" Black Oak, with scribe) bears N 72° W, 8.6 feet to the center of the tree. (Record to center = N78°W, 8.5 feet)
- The original bearing tree (now a 24" Laurel, with scribe) bears N55°E, 6.2 feet to the center of the tree.

From said pipe corner I established the following new bearing trees:

- A 16" Black Oak, scribed "CS-BT" bears S 24° W, 52.6 feet to the face of the lower blaze;
- A 16" Black Oak, scribed "CS-BT" bears S 66¾° E, 48.3 feet to the face of the upper blaze;
- An 18" Fir, scribed "CS-BT" bears N 13½° E, 32.6 feet to the face of the lower blaze;
- A 14" Pine, scribed "CS-BT" bears N 63° W, 25.2 feet to the face of the lower blaze.

August 11, 1969  
 F. Roberts, Deputy County Surveyor  
 O. Blankenship


**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 36 South, Range 4 West, W.M.

At the corner, found projecting 5 ins., 1½ ins. diam. iron pipe, with 1 ins. pipe inside with attached 2½ ins. diam. bronze cap marked:



As recorded on First re-establishment page 26, in 1969.

All bearing trees recorded on above noted re-establishment have been burned and/or destroyed in recent (1981) forest fire. Bearing trees marked in 1969 found:

- Fir, 21 ins. diam., dead and burnt, brs. Record: N13½°E, 32.6 feet to estimated lower face.
- Black Oak, 17 ins. diam., dead and burnt, brs. S66¾°E, 47.9 feet to center. Record: 48.3 feet.
- Burned Oak root crown brs. Record: S24°W, 52.6 feet.

There being no living trees available, set 5/8 x 30 ins. rebars, 24 ins. in the ground, with yellow plastic caps marked "Jackson C.S.":

- N13½°E, 31.92 feet.
- S2°E, 49.98 feet.
- N53°W, 19.75 feet.

Corner lies 20 feet South of draw C. S50°E and an estimated 100 feet N70°W, of the junction of two Southerly bearing draws.

June 8, 1982  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 20°  
P. -79