

FIRST RE-ESTABLISHMENT

GCDB 600500

Corner to Sections 11, 12, 13 and 14, Township 36 South, Range 4 West.

Found original BT to Southwest and Southeast with scribe visible; also, stump of original BT to Northeast together with mound of stone to mark corner.

Set 2"x36" galvanized pipe for corner,

From which:

- The original BT a 12" Black Oak plainly scribed bears South 33° West, 30.0 feet.
- Scribed a 20" Black Oak CS-BT which bears South 36°15' East, 116.9 feet.
- A 24" White Oak scribed CS-BT bears North 16° West, 115.5 feet;
- A 14" Fir scribed CS-BT bears North 79° East, 70.1 feet.

November 3, 1931
C. Z. Boyden, Deputy County Surveyor
L. Smith, Chainman
C. Bourne, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13 and 14, Township 36 South, Range 4 West, W.M.

Found badly mushroomed and 1 ins. deep in a ring of stones, the 2 ins. diam. iron pipe reported set on First re-establishment, page 4, in 1931. Set a 1 x 12 ins. galvanized iron pipe in the center of said found pipe, 10 ins. in the ground. In the top of said set pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W	
11	12
— —	
14	13
C.S.	
1986	

A found stump hole, with Oak remains alongside, of the original bearing tree marked by Ives and Hyde in 1854, brs. Record: S47°E, 22.44 feet to estimated face location.

Bearing trees marked on First re-establishment found:

- Fir snag, now 23 ins. diam. with double healed blazes, brs. Record: N79°E.
- Black Oak, now 28 ins. diam. with rotted center and double healed blazes, brs. Record: S36¼°E, 117.2 feet to center of tree at lower blaze.
- Black Oak, (record White Oak) now 34 ins. diam., brs. Record: N16°W, 116.5 feet to center of tree at root crown.

Mk new trees "CS" "BT" and measure to center of trees at lower blaze:

- Fir, 10 ins. diam., brs. N47½°E, 33.94 feet.
- Fir, 7 ins. diam., brs. S28½°E, 19.07 feet.
- Fir, 6 ins. diam., brs. S59°W, 21.41 feet.
- Pine, 22 ins. diam., brs. N31¾°W, 81.74 feet.

Corner lies on a wooded ridge, course N70°E, on a 46% Easterly slope.

November 20, 1986
D. Edwards
R. Romio

Edward McGinty
County Surveyor

V = 18½°
P.-329