

## FIRST RE-ESTABLISHMENT

GCDB 600600

Corner to Sections 1, 2, 11 and 12, Township 36 South, Range 4 West.

Found original BT to Northwest plainly scribed BT to Northeast damaged by fire, no scribe visible;  
also, stump hole of BT to Southwest

From which set a 2"x36" pipe for corner,

From which:

- A 26" Yellow Pine scribed CS-BT bears North  $44^{\circ}45'$  West, 172.2 feet;
- An 8" fir scribed CS-BT bears North  $82^{\circ}45'$  East, 86.0 feet;
- A 24" yellow Pine scribed CS-BT bears South  $28^{\circ}$  West, 65.5 feet;
- A 42" fir scribed CS-BT bears South  $22^{\circ}30'$  East, 76.6 feet.

November 3, 1931  
C. Z. Boyden, Deputy County Surveyor  
L. Smith, Chainman  
C. Bourne, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11 and 12, Township 36 South, Range 4 West, W.M.

Found projecting 3 ins., the 2 ins. diam. iron pipe reported set on First Re-establishment, page 4, in 1931. Inside of said pipe, set a 1 x 36 ins. galvanized iron pipe 22 ins. in the ground.

In the top of said 1 ins. diam. iron pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W	
2	1
— —	
11	12
C.S.	
1986	

Original bearing trees marked by Ives and Hyde in 1854 found:

- Fir shell, brs. Record: N70°W, 11.88 feet to estimated lower face.
- Fir stump, brs. Record: N55°E, 11.88 feet to estimated lower face.

Bearing trees marked on First re-establishment found:

- Fir snag, 46 ins. diam. with double healed blazes, brs. S20½°E, 75.0 feet. Record: S22½°E, 76.6 feet.

Bearing trees marked on Survey No. 2802 found and measured to center of tree at lower blaze:

- Fir snag, now 9 ins. diam. with double healed blazes, brs. N69°E, 23.34 feet. Record: N68°E, 23.5 feet.
- Fir, now 11 ins. diam. with double healed blazes, brs. S56¼°E, 31.54 feet. Record: S57°E, 31.8 feet.
- Fir, now 11 ins. diam. with double healed blazes, brs. S13¼°W, 7.40 feet. Record: S11°W, 7.55 feet.
- Madrone, now 11 ins. diam. with scribe marks including "2 3683" and "BT" visible in partially healed upper and lower faces, respectively, brs. N11½°W, 9.12 feet. Record: N13°W, 9.5 feet.

Mk new tree "CS" "BT":

- Fir, 7 ins. diam., brs. N45½°E, 19.59 feet to center of tree at lower blaze.

Corner lies in a wooded area, on a 60% Northeasterly slope, an estimated 100 feet North of the top of a ridge, course N45°W.

November 17, 1986  
D. Edwards  
T. Newcomb

Edward McGinty  
County Surveyor

V = 18°  
P. -314