

## FIRST RE-ESTABLISHMENT

GCDB 600700

Section corner on Township line, Sections 35 and 36, Township 35 South, Range 4 West and Sections 1 and 2, Township 36 South, Range 4 West.

Found Black Oak stump plainly scribed BT for original BT to northeast. Also found Laurel sprouts and Black Oak sprouts to indicate the location of the southwest and southeast BTs

From which evidence:

- Set a 2"x36" galvanized iron pipe 28" in the ground for corner

From which

- a 12" Laurel scribed CS-BT bears N. 81°W. 55.5 feet;
- Scribe an 8" Laurel CS-BT which bears S. 46° W. 28.7 feet;
- Scribe an 8" Laurel CS-BT which bears S. 32° E. 24.1 feet;
- Scribe an 8" Black Oak CS-BT which bears N. 10° E. 26.6 feet;

February 15, 1952

C. Z. Boyden

John Cox

Dean W. Pruett

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 600700

Section corner common to Sections 35 and 36, Township 35 South, Range 4 West and Sections 1 and 2, Township 36 South, Range 4 West, W.M.

Found projecting 6 ins., the 2 ins. diam. iron pipe reported set on first re-establishment, page 9, in 1952. In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T35S R4W	
35	36
-----	
2	1
C.S.	
T36S	
1988	

Bearing trees marked on said first re-establishment found with double healed blazes and measured to center of trees at lower blaze:

- Black Oak, now 13 ins. diam., brs. N12½°E, 27.4 feet. Record: N10°E, 26.6 feet.
- Madrone, now 14 ins. diam., brs. S28°E, 24.35 feet. Record: S32°E, 24.1 feet.
- Madrone, now 11 ins. diam., brs. S49°W, 28.86 feet. Record: S46°W, 28.7 feet.
- Madrone, now 12 ins. diam., brs. Record: N81°W, 55.53 feet.

Corner lies in shallow draw, course N48°W, 100 feet to dirt road, course N80°W.

April 5, 1988  
D. Edwards, Tech.  
T. Newcomb, Tech.

Edward McGinty  
County Surveyor

V = 18¾°

P.-124