

## FIRST RE-ESTABLISHMENT

GCDB 640200

Quarter corner to Sections 25 and 36, Township 36 South, Range 4 West.

Found point of old stake surrounded with stones. Original bearing tree with old axe marks bears South 68° East, 30.4 feet, also dead 30" fir with scribe legible bears North 25° West, 4.0 feet (Note: official government notes call for 18" yellow pine).

Set a ½"x24" iron pipe at the exact location of old stake as found,

From which:

- A 6" Black Oak scribed CS-BT bears South 54° West, 18.7 feet;
- An 18" White Oak scribed CS-BT bears North 57¾° East, 41.2 feet;
- A cross on top of solid rock outcrop bears North 87° West, 9.2 feet.

January 17, 1944  
C. Z. Boyden  
J. H. Cushman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 640200

Quarter corner common to Sections 25 and 36, T36S, R4W, W.M.  $V = 18\frac{1}{2}^\circ$

Found  $\frac{1}{2}$  ins. diam. iron pipe, projecting 2 ins., set on first re-establishment by C. Z. Boyden in 1944.

Over said pipe, I drove a 1x36 ins. GI pipe 28 ins. in the ground with a  $2\frac{1}{2}$  ins. bronze disc marked:

T36S R4W  
25  
 $\frac{1}{4}$ S —  
36  
Jackson County 1974

BTs recorded by Boyden found as follows:

- A White Oak, 17 ins. diam., with healed blazes, bears record,  $N57\frac{3}{4}^\circ E$ , 41.2 feet to estimated face of upper blaze. Re-measured 42.0 feet to center of tree.
- A White Oak, 9 ins. diam., with healed blazes, bears record,  $S54^\circ W$ , 18.70 feet to estimated face of upper blaze. Re-measured 18.95 feet to center of tree.

A cross on the NW point of a rock outcrop, marked by Boyden, bears  $N87^\circ W$ , 9.17 feet. Record,  $N87^\circ W$ , 9.2 feet.

An original BT marked by Ives and Hyde in 1854, a Fir, now a 30 ins. diam. snag, 12 feet high, scribed " $\frac{1}{4}$ S" bears record,  $N25^\circ W$ , 3.96 feet to scribed face.

A down and rotted Black Oak found at record location of original SE BT.

I mound stones around corner, marked the following trees C.S. BT and take measurements to center of trees at lower blaze:

- A Douglas Fir, 11 ins. diam., bears  $N45\frac{1}{2}^\circ E$ , 54.25 feet.
- A White Oak, 8 ins. diam. bears  $S14\frac{1}{2}^\circ W$ , 14.75 feet.

Corner lies on N-S blazed line, 7 feet West of down N-S fence line.

June 11, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor