

FIRST RE-ESTABLISHMENT

GCDB 640400

Quarter corner common to Sections 13 and 24, Township 36 South, Range 4 West, W.M.

$V = 19\frac{1}{2}^\circ$

From the following evidence at the location described below, I set a 1x36 ins. G.I. pipe 24 ins. in the ground with a 2½ ins. bronze disc marked:

Jackson County 1975

T36S R4W

13

¼S —

24

- An original BT marked by Ives and Hyde in 1854, a White Oak, now 13 ins. diam., containing partial scribed "¼" in opened upper face, bears record S73°E, 56.10 feet.
- A possible original BT, now a 20 ins. diam. WHITE OAK stump, bears N83°W, 59.0 feet. Record, N75°W, 58.74 feet.

I mound stones around corner, marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- The Southerly branch, 12 ins. diam., of a double White Oak, bears N10½°E, 53.35 feet.
- A White Oak, 9 ins. diam., bears S63°E, 27.54 feet.

Corner lies N75°W, 11.8 feet from a blazed White Oak, 6 ins. diam., and 73 feet West of stream.

March 5, 1975
K. Weaver
G. Cunningham

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640400

One quarter corner common to Sections 13 and 24, Township 36 South, Range 4 West, W.M.

At the corner, found projecting 12 ins. in mound of stone, the 1 in. diam. iron pipe, with 2½ ins. diam. bronze disc marked:

JACKSON COUNTY 1975

T36S R4W

13

¼S —

24

As recorded on First re-establishment, page 34, in 1975.

Bearing trees marked on First re-establishment, now burned by recent forest fire, found and measurements taken to center of trees at lower blaze:

- White Oak, 16 ins. diam., brs. N10°04'E, 53.60 feet. Record: 10½°E, 53.35 feet.
- White Oak, 9 ins. diam., brs. S63°10'E, 27.54 feet. Record: S63°E.

An original bearing tree, recorded by Ives and Hyde in 1854, a White Oak, now 13 ins. diam., with burned out faces, brs. S73°E, 56.2 feet to center of tree. Record: 56.1 feet.

As all trees in vicinity of corner have been fire damaged, set 5/8 x 30 ins. rebars, with yellow plastic caps marked "JACKSON C.S.":

- N9°58'E, 51.60 feet, projects 6 ins.
- S63°25'E, 26.42 feet, projects 9 ins.
- feet fiberglass post brs. N65°E, 5 feet.

Corner lies about 73 feet West of Northerly gulch and an estimated 300 feet, N60°W, of (prospect) mine.

October 21, 1981

R. Frost

R. Templin

Edward McGinty

County Surveyor

V = 19°

P.-170