

## FIRST RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 36 South, Range 4 West, W.M.

Found firmly set and projecting 6 ins., the 1 in. diam. iron pipe set on Survey No. 2802, in 1965.

\*Oak fragments, some with axe work apparent, occupy the vicinity where the original Northwest bearing tree, marked by Ives and Hyde in 1854 and reported found on Survey No. 2802, would have been.

Bearing trees marked on Survey No. 2802 found:

- Fir, now a 17 ins. diam. snag with double healed blazes, brs. Record: N12¼°E, 21.90 feet to center of tree at lower blaze. Record distance 22.45 feet.
- Black Oak, now 20 ins. diam. with double healed blazes, brs. Record: S73¾°E, 41.15 feet to center of tree at lower blaze. Record distance 41.8 feet.

Mk new tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Fir, 16 ins. diam., brs. N19¼°E, 24.39 feet.
- Placed location poster on a 8 ins. diam. Fir, an estimated 850 feet East of corner.

Corner lies on a 60% Southerly slope 15 feet North of a draw, course S70°E.

November 19, 1986  
D. Edwards  
R. Romio

Edward McGinty  
County Surveyor

V = 19°  
P. -317

### \*NOTE:

In the top of said pipe, set in concrete, a 2½ ins. diam. brass cap marked:

T36S R4W  
1  
¼S —  
12  
C.S.  
1986