


SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 700340

Quarter corner common to Section 24, Township 36 South, Range 4 West and Section 19, Township 36 South, Range 3 West, W.M.

Found 6 ins. deep the 3 ins. diam. standard BLM brass cap marked:



Set over found 5/8 ins. diam. iron rod set on Survey No. 3711, dated 1968.

Found flush, State Highway Dept. reference, a 2 1/2 ins. diam. brass cap set in concrete 6 ins. square, center punch:

- Bears S72°41'30"W, 397.41 feet. BLM Record: 397.32 feet. This is Sta. 747+39.63 PCs.
- Bears N77°50'08"E, 202.57 feet. BLM Record: N77°50'E, 202.62 feet. This is Sta. 753+39.63 pt.

Found a smooth 5/8 ins. diam. iron pin projecting 1 ins., bears N77°50'13"E, 207.28 feet.

Set flush 5/8 x 24 ins. diam. rebar with aluminum cap marked "Jackson CS", bears N0°54'53"W, 20.49 feet, which is 14 1/2 feet south from edge of concrete of north bound lane.

Corner lies in the middle of freeway medium and under the east side of power lines crossing the freeway course S10°W/N10°E.

June 9, 1997
T. Newcomb, Tech.

Roger Roberts
County Surveyor

P. -51