

## FIRST RE-ESTABLISHMENT

GCDB 700540

Quarter corner common to Section 12, Township 36 South, Range 4 West and Section 7, Township 36 South, Range 3 West.

Found the 1" iron pipe set for corner by surveyor Robert M. Thompson while executing the survey for the proposed subdivision plat of HIGHLAND MEADOWS.

In the exact position of said pipe, set a 1"x36" galvanized iron pipe with bronze cap stamped:

T36S R3&4W  
¼ Cor. 12 | 7 C.S.  
1965

Set 30" in the ground for corner.

From which:

- The original witness tree (now a 20" Black Oak with old axe marks, and the center badly rotted) bears North 7° West, 21.7 feet to the probable face;
- The center of the pitched core of a Y. Pine stump underneath the ground bears South 12° East, 37.6 feet;
- A 20" Yellow Pine, found scribed "BT S12 316" on one blaze bears South 80° West, 23.4 feet to the face of the blaze;
- Found a 7"x12"x? basalt stone with cross which bears Easterly 2.2 feet;
- Found a 5/8" copper-coated ground rod which bears Easterly 2.8 feet.

Scribed a 16" Black Oak, "CS-BT" which bears North 25° East, 41.6 feet to the face of the lower blaze.

June 8, 1965  
L. D. Pinkham, Deputy County Surveyor  
Lloyd Hart

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700540

Quarter corner common to Section 7, Township 36 South, Range 3 West and Section 12, Township 36 South, Range 4 West, W.M.

Found the 1 ins. diam. galvanized iron pipe set on the first re-establishment, dated 1965, with 2½ ins. diam. brass cap marked:

T36S R3&4W  
¼ 12 | 7 CS  
Cor.  
1965

Protruding 3 ins. above the ground from which First Re-establishment references found:

- Black Oak 18 ins. diam., dead and down with "CS" scribe visible on exposed upper face, bears N23°E, 42.2 feet to the center of root hole. Record bearing; N25°E.
- ⅝ in. diam. iron rod protruding 3 ins. above the ground bears N86°E, 2.82 feet.
- Stone 7x12x? ins. with an "X" on top bears S88½°E, 2.2 feet.

Mk new trees "CS" "BT" and measure to the center of tree at lower blaze:

- Madrone 7 ins. diam., bears S49¼°E, 11.6 feet.
- Madrone 7 ins. diam., bears S55¾°W, 26.3 feet.

Corner lies N35°E, approximately 50 feet of the intersection of dirt roads bearing S75°E, S10°E, S80°W, N36°W, and between power lines.

August 22, 1989  
S. Beecher, Tech.  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

V = 17°  
P.-178

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

### THIRD RE-ESTABLISHMENT

GCDB 700540

Quarter corner common to Sections 7, Township 36 South, Range 3 West and Section 12, Township 36 South, Range 4 West, W.M.

Found projecting 6 ins., set on first re-establishment, dated 1965 a 1 in. diam. galvanized iron pipe with a 2½ ins. diam. brass cap marked:

T36S R3&4W  
¼ 12 | 7  
Cor 1965

Found single remaining original bearing tree, recorded by Ives and Hyde in 1854 now a stump hole brs. recorded (1965); N7°W, 21.70 feet to estimated face.

Bearing trees and references found or marked on first re-establishment found:

- Stump hole brs. Record: S80°W, 23.40 feet to estimated face.
- Stump hole brs. Record: N25°E, 41.60 feet to estimated face.
- Basalt stone projecting 12x6x4 ins. with a small "+" on top brs. N86½°E, 2.20 feet. Record: Easterly.
- 5/8 ins. copper rod projecting 4 ins. brs. N82°E, 2.83 feet. Record: Easterly, 2.80 feet

Bearing trees marked on second re-establishment, dated 1989 found with unhealed and burned faces and measured to the center of tree at lower blaze:

- Dead Madrone 6 ins. diam., brs. S54½°W, 26.20 feet. Record: S55¾°W, 26.30 feet.
- Dead Madrone 6 ins. diam., brs. S51½°E, 11.65 feet. Record: S49¼°E, 11.60 feet.

Set new references:

5/8 x 24 ins. rebar with aluminum cap marked "Jackson County CS" set flush:

- Brs. N6°W, 20.14 feet with a 5½ feet fence post set directly behind.
- Brs. N35½°E, 11.89 feet with a 5½ feet fence post set directly behind.
- Brs. S5½°E, 10.40 feet.

Corner lies in area burned by fire between August 3 to August 6, 1992.

February 25, 1993  
T. Newcomb, Tech.  
J. Burgess, Tech.

Verlyn Thomas  
County Surveyor

V = 17½°

p-28