

FIRST RE-ESTABLISHMENT

GCDB 700700

Section corner common to Section 36, Township 35 South, Range 4 West, Section 31, Township 35 South, Range 3 West, Section 1, Township 36 South, Range 4 West, and Section 6, Township 36 South, Range 3 West, W.M. $V = 19^\circ$

Found, in mound of stone the 1x30 ins. black iron pipe, projecting 8 ins., set on survey no. 735, dated 1955 (on file).

I replaced the above with a 1x36 ins. G.I. pipe set 30 ins. in the ground with 2½ ins. bronze disc marked:

Jackson County 1975
T35S
36 | 31
— | —
1 | 6
R4W R3W
T36S

Original BTs recorded by Ives and Hyde in 1854, found as follows:

- A White Oak, 13 ins. diam., containing reverse impression of scribed "BT", bears $N36\frac{1}{2}^\circ E$, 53.83 feet to scribed face. Record: $N37^\circ E$, 54.12 feet.
- A rotted, sawed, Pine stump, 17 ins. diam., bears Record: $S17^\circ E$, 47.52 feet to estimated face.
- A Pine stump, 31 ins. diam., with exposed and burned faces, bears Record: $S15\frac{1}{2}^\circ W$, 80.52 feet to upper face.
- A White Oak, 12 ins. diam., with healed blazes, bears $N63\frac{1}{2}^\circ W$, 61.3 feet to center of tree at lower blaze. Record, $N64\frac{1}{4}^\circ W$, 61.38 feet.

I deposit found pipe alongside corner, marked new trees C.S. BT and take measurements to center of trees at lower blaze:

- A Ponderosa Pine, 8 ins. diam., bears $N45^\circ E$, 38.75 feet.
- An Incense Cedar, 7 ins. diam., bears $S41^\circ E$, 54.41 feet.
- A Ponderosa Pine, 15 ins. diam., bears $S85^\circ W$, 35.35 feet.
- A Douglas Fir, 8 ins. diam., bears $N7^\circ W$, 10.08 feet.

Corner lies about 35 feet West of center of dirt road. Spring branch bears East, 17.0 feet.

April 30, 1975

B. Malotte

R. Frost

Approved by: Edward McGinty
County Surveyor