

FIRST RE-ESTABLISHMENT

DLC37NE

GCDB 943010

Northeast corner of DLC 37, Township 36 South, Range 4 West.

Found original BT stump to Northwest, from which set 1½"x36" galvanized pipe for corner,

From which:

- A 6" White Oak scribed CS-BT bears North 29°30'West, 18.9 feet;
- A 36" Black Oak scribed CS-BT bears North 79°35' East, 400.4 feet;
- An 18" Laurel scribed CS-BT bears South 31°35' East, 172.5 feet.

March 19, 1929

C. Z. Boyden, Deputy County Surveyor

O. H. Tice, Ed Judd, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC37NE

GCDB 943010

Northeast Donation Land Claim No. 37, located in Section 26, Township 36 South, Range 4 West, W.M.

Found, at the corner, projecting 2 ins. the 1½x36 ins. G.I. pipe (which I remove from the ground and replace upside down) set on first re-establishment in 1929.

Inside found pipe I set a 1x36 ins. G.I. pipe 34 ins. in the ground with a 2½ ins. diam. bronze disc marked:

JACKSON COUNTY 1980
T36S R4W
DLC
N.E.
37

A bearing tree marked on first re-establishment, a White Oak, now 15 ins. diam., with healed blazes, located on East-West cyclone fence line brs. Record: N29½°W (basis of bearing) 18.9 feet to estimated face. Re-measured 19.15 feet to center of tree at base.

I set new references; 5/8 x 36 ins. rebars flush with the surface of the ground with yellow plastic caps marked:

"JACKSON C.S."

- S32°57'E, 12.62 feet, located at Northeast corner of building (described below).
- S78°50'W, 30.58 feet, located 1 feet North of the center of 16 ins. diam. locust tree.

Corner lies approximately 25 feet above and 60 feet West of Footh Creek and 8.2 feet North of the North side of log slab sided building at 3242 Rogue River Drive.

June 3, 1980

R. Frost
D. Danielsen

Approved by: Edward McGinty
County Surveyor