

**FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 30 ONLY  
GCDB 100240**

One quarter corner to Section 30 only, on the West line, in Township 38 South, Range 1 West.

Found the 1½-inch diameter iron pipe, projecting 6 inches in mound of stone, set for the corner on Survey 1702, dated 1961.

To perpetuate this position, in the top of found pipe, set in cement, brass cap marked:

T38S  
|  
R1W  
|  
C.S. S30  
|  
1981

- Bearing tree marked by W. N. Gibbs in 1909, a Douglas Fir, now 17-inch diameter, scribed "¼ S 30 BT" in opened face, bears S68°E, 4.85 feet to scribed face. Re-measured; 5.22 feet to center of tree. Record: 5.94 feet.
- Bearing tree marked on Survey 1702, now a Fir stump, 16-inch diameter, containing scribed "BT" bears N84½°E, 29.5 feet to center. Record: 30.36 feet.
- A bearing tree, now of record, a Douglas Fir, 12-inch diameter containing scribe marks in partially open face, bears S64½°W, 8.65 feet to center.

**SEE ALSO Jackson County Project File No. 81-12.**

The (brass cap) proportion quarter corner of Section 25, Township 38 South, Range 2 West, per Survey No. 1702, bears S0°18'W, 42.41 feet. Record: 41.58 feet.

April 20, 1981  
J. Swanson  
R. Frost

Edward McGinty  
County Surveyor

V = 18°  
P. -67