

FIRST RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to Section 18, Township 38 South, Range 1 West, and Section 13, Township 38 South, Range 2 West, W.M.

At the corner, found projecting 4 inches, the $\frac{5}{8}$ -inch diameter rebar reported on Survey No. 4044, dated 1969. Atop said rebar, set yellow plastic cap marked: JACKSON C.S.",

From which:

- An original bearing tree recorded by Ives and Hyde in 1854, now an Oak stump shell, 14-inch diameter, with opening in area of faces, bears Record: S44°W, 13.86 feet to estimated face.
- Oak stump remains, including portion of axed face, containing scribe mark, found at record (survey No. 1357, "N73°E, 19.1" feet.) location of original Northeast BT.

Reference trees blazes on Survey No. 1357, dated 1960 found as follows:

- The stump, 13-inch diameter of a down and rotted White Oak, bears S71°45'E, 19.2 feet to estimated face. Record: S72¼°E.
- White Oak, 24-inch diameter, with healed blazes, bears N50°15'W, 25.4 feet to center of tree at upper blaze; 25.3 feet to center of tree at lower blaze. Record: N50°W, 25.6 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Oak, 14-inch diameter, bears S8°35'E, 9.30 feet.
- White Oak, 5-inch diameter, bears S53°07'W, 39.25 feet.

Corner lies on North (35%) slope, about 130 feet South of road, C. East-West and 9 feet West of fence line C. N10°W.

July 25, 1984
R. Frost
E. McGinty

Edward McGinty
County Surveyor

P. -94

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to Section 18, Township 38 South, Range 1 West and Section 13, Township 38 South, Range 2 West, W.M.

Found projecting 4 inches, the $\frac{5}{8}$ -inch rebar as found on First Re-establishment, in 1984, with the yellow plastic cap marked "Jackson County" set in 1984.

Removed plastic cap and set over rebar a 1x36-inch Galvanized iron pipe 32 inches in the ground with a 2½-inch diameter brass cap marked:

T38S
¼S
R2W 13 | 18 R1W
CS
1989

Single remaining bearing tree marked on First Re-establishment found:

- White Oak, 14-inch diameter with scribe marks "CS" "BT" visible on partially healed blazes bears Record: S08°35'E, 9.38 feet.

Marked new trees "CS" "BT" and took measurements to the center of tree at lower blaze:

- White Oak, 6-inch diameter bears N61°44'W, 23.20 feet.
- White Oak 4-inch diameter, bears N03°58'W, 19.00 feet.

Corner lies on North slope 9 feet West of North-South fence line and 20 feet East of an area that has been cleared. Dirt road bears North 130 feet.

November 3, 1989
T. Newcomb, Tech.
S. Beecher, Tech.

Verlyn Thomas
County Surveyor

P. -217