

## FIRST RE-ESTABLISHMENT

GCDB 100500

Sections corner common to Sections 12 and 13, Township 38 South, Range 2 West, and Sections 7 and 18, Township 38 South, Range 1 West, W.M.

Found the original NE witness tree with negative scribe marks plain. Also found the original NW witness tree down with negative scribe marks plain and the stump holes for the original SE and SW witness trees.

Set a 1" x 36" galvanized iron pipe 34" in the ground with 2½" bronze cap stamped:

T38S R1&2W	
12	7
13	18
CS	
1960	

For corner, from which:

- The original witness tree (now a 14" Black Oak) bears N73°E, 50.8 feet.
- The stump hole of the original NW witness tree bears N41°W, 12.5 feet.

I marked new trees as follows:

- A 6" White Oak scribed CS-BT bears S40°E, 31.6 feet.
- An 8" White Oak scribed CS-BT bears S67¾°W, 69.0 feet.
- A 4" White Oak scribed CS-BT bears N48¼°W, 18.7 feet.
- A 4" White Oak scribed CS-BT bears N41½°E, 13.5 feet.

Var. 20°E.  
August 25, 1960  
M. E. Boyden  
F. A. Roberts

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 100500

Section corner common to Sections 12 and 13, Township 38 South, Range 2 West and Sections 7 and 18, Township 38 South, Range 1 West, W.M.

Found projecting 2 inches, the 1-inch diameter iron pipe with 2½-inch diameter brass cap marked:

T38S R1 & 2W	
12	7
13	18
C.S.	
1960	

As recorded on First re-establishment, page 23, in 1960. Basis of bearing, GLO North on South line.

Bearing trees marked in 1960 found and measured to center of trees at lower blaze:

- White Oak, 8-inch diameter with healed blazes bears S40°29'E, 31.85 feet. Record: S40°E, 31.6 feet.
- White Oak, 9-inch diameter with healed blazes bears S68°40'W, 69.10 feet. Record: S67¾°W, 69.0 feet.
- Bearing trees Northerly of corner have been destroyed by recent clearing preparatory to the planting of a new orchard.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Oak, 5-inch diameter, bears S80°06'E, 65.1 feet.
- White Oak, 5-inch diameter, bears S13°54'W, 4.9 feet.
- Set 5/8 x 24-inch rebar, flush, with yellow plastic cap marked "Jackson C.S.", bears S0°29'W, 8.52 feet.
- The (brass cap) quarter corner of Sections 7 and 12 bears North 2649.28 feet.
- The (brass cap) corner of Sections 1, 6, 7 and 12, bears North 5298.56 feet.

Corner lies at South edge of large field, an estimated 500 feet North of hilltop and on feet North of old wire and picket fence c. East-West.

September 11, 1985

R. Frost

S. Nelson

Edward McGinty

County Surveyor

P. -256