

FIRST RE-ESTABLISHMENT

GCDB 200300

Section corner common to Sections 19, 20, 29 and 30, Township 38 South, Range 1 West, W.M.

At the corner, found projecting 4 inches, a 5x5x12-inch Granite stone. Reference C. A. Nutter (civil engineer) 1929 survey, now filed in Ancient Survey Book A-2, Jackson County Surveyor Records.

Replace said stone with and deposited it alongside, a 1 x 36-inch G.I. pipe, set 30 inches in ground with a 2½-inch diameter bronze cap marked:

JACKSON COUNTY 1981

T38S R1W

19	20
30	29

Unrecorded reference trees (Nutter survey?) found and measurements taken to center of trees:

- Laurel, 15-inch diameter with healed blazes, bears N7°E, 37.6 feet.
- Douglas Fir, now dead, 14-inch diameter, with healed blazes, bears S43°W, 73.40 feet.
- Black Oak, 6-inch diameter with healed blazes, bears N60°45'W, 25.0 feet.

Bearing trees marked on Survey 2116, dated 1963, found as follows, with measurements taken to center of trees at lower blaze:

- Laurel, 10-inch diameter containing bark scribe marks including "T38S" and "BT", bears Record: N44°E, 48.84 feet on slope. Re-measured; 48.06 feet.
- Douglas Fir, 11-inch diameter, with healed single blaze bears Record: S76°E, 23.10 feet.
- Laurel, 14-inch diameter, with healed single blaze bears Record: S19°W, 14.52 feet.
- Douglas Fir, 12-inch diameter, with healed single blaze, bears N46°W, 26.40 feet. Record: N64°W.

Corner lies on North-South fence line, about 30 feet North of small draw c. West.

April 16, 1981

R. Frost

R. Templin

Edward McGinty

County Surveyor

P.-66