

**FIRST RE-ESTABLISHMENT**

**GCDB 200340**

Quarter corner to Sections 19 and 20, Township 38 South, Range 1 West, W.M.

Found the witness tree in Section 20 intact.

Corner marked with a blue granite stone and set new witness tree in Section 19: A 15" Black Oak which bears S57°W, 100.7 feet from the  $\frac{1}{4}$  corner.

March 16, 1914  
A. T. Brown,  
Deputy County Surveyor

H. Ling, Chainman  
P. Murphy, Chainman

## SECOND RE-ESTABLISHMENT

GCDB 200340

Quarter corner common to Section 19 and 20, Township 38 South, Range 1 West, W.M.

Found at the corner, 6 inches deep, the 1½-inch diameter iron pipe set on Survey No. 2116 in 1963.

In the top of said pipe, set 2½-inch diameter brass cap in concrete, marked:

T38S R1W  
¼S 19 | 20 C.S.  
1981

The single remaining bearing tree recorded by Ives and Hyde in 1854, now a dead topped Laurel, 30-inch diameter, scribed "¼S" in exposed face bears Record: N45°E, 25.08 feet, to scribed face.

A found smooth iron pin, ⅝-inch diameter, flush with the ground, bears North, 14.06 feet.

Set new references: Rebars, ⅝-inch diameter, 30 inches long, with yellow plastic caps marked: "Jackson C.S." flush, on East-West fence line:

- S40°19'E, 23.95 feet.
- S45°19'W, 26.00 feet.

Corner lies about 2 feet North of middle of Griffin Creek Road.

April 14, 1981  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 19½°  
P.-62

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

**THIRD RE-ESTABLISHMENT**

**GCDB 200340**

Quarter corner common to Sections 19 and 20, Township 38 South, Range 1 West, W.M.

Found at the corner position, 7 inches deep, the 2½-inch diameter brass cap set on Second Re-establishment in 1981, marked:

T38S R1W  
¼ S19 • 20 CS  
1981

Set directly above said monument, in concrete and 1-inch deep, a 2½-inch diameter brass cap, marked:

JACKSON COUNTY SURVEYOR  
T38S R1W  
¼  
S19 • S20  
2003

References recorded on SECOND Re-establishment in 1981, found and re-measured:

- Single remaining original bearing tree recorded by Ives and Hyde in 1854, a madrone now 30-inch diameter with scribe marks "¼S" on exposed face, bears N45°E, 26.02 feet to center of tree at lower blaze. Record: 25.08 feet to face.
- 5/8-inch diameter rebars with yellow plastic caps found flush and marked "JACKSON C.S." br.:
  - ▶ S45°19'W, 25.98 feet. Record: 26.00 feet.
  - ▶ S39°42'21"E, 23.75 feet. Record: S40°19'E, 23.95 feet (pin bent westerly).

Set 5/8 x 30-inch rebar, exp. 1 inch with 1½-inch diameter aluminum cap marked

JACKSON COUNTY  
  
SURVEYOR

Bears N72°04'34"W, 68.50 feet.

Corner lies near the middle of Griffin Creek Road, approximately 350 feet westerly of centerline intersection with Coleman Creek Road,

May 5, 2003

H. Durkee

T. Newcomb

Roger R. Roberts

Jackson County Surveyor

P. - 57