

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 32 ONLY
GCDB 240100**

South quarter corner Section 32, Township 38 South, Range 1 West, W.M. $V = 20^\circ$

Found $\frac{5}{8}$ -inch iron pin projecting 1 inch from ground in pile of stones and reference trees blazed per registered Survey No. 4075 dated July 1969. Found partial scribe of original BT (Original record was "redwood") bearing $S81^\circ E$, 18.5 feet.

From which evidence and at the exact same spot as the $\frac{5}{8}$ " iron pin, I set a 1 x 36-inch G.I. Pipe, 32 inches in the ground with a $2\frac{1}{2}$ -inch bronze disc marked:

T38S R1W
1973 $\frac{1}{4}$ S32
———
C.S.
T39SR1W

From which:

- A Douglas Fir, 8" diameter bears North, 35.3 feet to center of tree at lower blaze marked C.S. BT.
- A Douglas Fir, 10" diameter bears $N89^\circ W$, 37.5 feet to center of tree at lower blaze, marked C.S. BT.
- A found $\frac{1}{2}$ inch iron pin bears $N89^\circ 50' E$, 140.20 feet.

March 23, 1973
Bob Malotte
Ron Frost

Approved By: Edward McGinty
County Surveyor