

FIRST RE-ESTABLISHMENT

GCDB 240300

Quarter corner common to Sections 20 and 29, Township 38 South, Range 1 West, W.M.

Found 14 inches deep, an 11 x 9 x 6-inch stone with a hole drilled for the corner point, apparently set by one Chas. Nutter, on a survey filed at the last page of the County Surveyor's Ancient Surveys Book A2, performed in November 1929, and reported found on Survey No. 2116, in March of 1963.

Replace said stone with and deposit it alongside of, a 1 x 36-inch Galvanized iron pipe, 29 inches in the ground. In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T38S R1W
20
¼S —
29
C.S.
1986

Place a 2-inch diameter iron pipe, found alongside said stone as reported on Survey No. 2116, alongside new pipe and cap.

No trace of the original bearing trees now exists, although it is likely that Nutter had the originals, as he makes the subject corner an angle point along the South line of Section 20.

Bearing trees marked on Survey No. 2216 found:

- Madrone, now 14-inch diameter with deteriorating bark scribing visible, bears Record: S24°W, 29.30 feet to center of tree at lower blaze (Record: 29.70 feet.)
- Black Oak, now 18-inch diameter with single healed blaze, bears Record: N31°W, 14.52 feet to center of tree at lower blaze.

Scribe a new tree "CS" "BT" and measure to center of tree at lower blaze:

- Fir, 13-inch diameter bears S7½°W, 31.87 feet.

Corner lies 30 feet West of the middle of a dirt road, course North-South, and approximately 30 feet East of a small creek, course N30°W.

October 29, 1986
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 19°
P.-294