

FIRST RE-ESTABLISHMENT

GCDB 300240

Quarter corner common to Sections 28 and 29, Township 38 South, Range 1 West, W.M.

Found projecting 2 inches, the 3/4 x 1/2 inches square iron rod reported on Survey No. 801 in 1956.

Set a 1 x 36-inch Galvanized iron pipe directly over found square rod, 30 inches in the ground, with a 2 1/2-inch diameter brass cap marked:

T38S R1W
1/4S
29 | 28
C.S.
1986

- The only remaining original bearing tree recorded by Ives and Hyde in 1854, a Black Oak, now 16-inch diameter, with scribed "1/4S" and "BT" visible in the exposed faces bears record N70°W, 21.12 feet to lower face.
- A reference tree noted on Survey No. 801, dated 1956, a Laurel, now 8-inch diameter with two partially healed un-scribed faces, bears N41°E, 25.35 feet to center of tree at lower blaze.
- A reference tree noted on Survey No. 2116, dated 1963, a Douglas Fir, now 15-inch diameter, with single healed blaze bears N81 1/4°E, 42.65 feet to center of tree at bottom of blaze. (Record: N82°E, 42.24 feet.).

Scribe new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Pine, 7-inch diameter, bears S72 1/2°E, 12.87 feet.
- Northerly fork, 10-inch diameter of a double Madrone, bears S24 1/2°W, 20.71 feet.

Corner lies on a moderate Southeast slope, 6 inches East of a North/South fence line, along logged area to the West.

August 20, 1986
R. Romio
T. Newcomb

Edward McGinty
County Surveyor

V = 18°
P.-220