

FIRST RE-ESTABLISHMENT

GCDB 300400

Re-establish corner Sections 17, 16, 20, 21, Township 38 South, Range 1 West.

Set a 2"x 36" galvanized iron pipe 30" in the ground for corner at the exact location of an old stake which is the recognized corner, which also checks the official record from the remains of original BTs to NE and NW with no scribe visible.

- Scribe a 26" White Oak CS-BT which bears S23¼°W, 50.7 feet.
- Scribe a 4" White Oak CS-BT which bears S4¾°E, 54.7 feet.
- Scribe a 10" White Oak CS-BT which bears N11½°E, 93.0 feet.

December 19, 1936
C. Z. Boyden,
Deputy County Surveyor

C. I. Bourne, Chainman

SECOND RE-ESTABLISHMENT

GCDB 300400

Section corner common to Sections 16, 17, 20 and 21, Township 38 South, Range 1 West, W.M.

Found the 2" iron pipe exposed 6" as set for corner on the First re-establishment by Deputy County Surveyor, C. Z. Boyden on December 19, 1936.

From which found the references established on the First re-establishment as follows:

- The Southwest bearing tree is down and dead with "BT" scribe visible. The location of the stump hole checks the re-establishment record.
- A 6" White Oak, scribed "CS-BT" with $30 \pm$ growth rings over face, marked on the First re-establishment bears $N77\frac{1}{4}^{\circ}W$, 40.6 feet to the face of the lower blaze. This tree is shown on C. Z. Boyden 1936 re-establishment field notes but was omitted from the typed record, (Record: 4" White Oak, $N77\frac{1}{4}^{\circ}W$, 40.6 feet.)

From said pipe corner, I establish the following new references:

- A 13" Laurel, scribed "CS-BT", bears $S77\frac{1}{4}^{\circ}E$, 56.1 feet to the face of the upper blaze.
- An 11" Laurel, scribed "CS-BT", bears $N67\frac{1}{4}^{\circ}E$, 72.4 feet to the face of the upper blaze.
- A 7" White Oak, scribed "CS-BT", bears $N86\frac{1}{4}^{\circ}W$, 20.6 feet to the face of the lower blaze.
- An 8" White oak, scribed "CS-BT", bears $S37^{\circ}W$, 36.6 feet to the face of the lower blaze.

May 28, 1969

G. Kaiser

J. Black

Approved by:

M. E. Boyden,

County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 300400

Section corner common to Sections 16, 17, 20 and 21, Township 38 South, Range 1 West, W.M.

Found projecting 4 inches, the 2-inch diameter iron pipe set on First Re-establishment, page 8, in 1936.

In the top of said pipe set in concrete, a 2½-inch diameter brass cap marked:

T38S	R1W
17	16
20	21
C.S.	
1987	

No trace of original bearing trees.

Bearing trees marked on said First Re-establishment found:

- White Oak, 23-inch diameter shell lying on ground with CS-BT scribes visible, lies in Southwest quadrant.
- White Oak, now 7-inch diameter with scribed "CS" visible in partially healed upper blaze, bears Record: N77¼°W, 40.6 feet to center of tree at lower blaze. Record distance; 40.6 feet to face.

Bearing trees marked on Second re-establishment, page 48, in 1969 found with double healed blazes and measured to center of trees at lower blaze:

- Madrone, the more southerly fork of a triple tree, and now 16-inch diameter, bears N66¾°E, 73.7 feet. Record: N67¼°E, 72.4 feet to upper face.
- Madrone, now 18-inch diameter, bears S76¾°E, 56.9 feet. Record: S77¼°E, 56.1 feet to upper face.
- White Oak, now 11-inch diameter, bears S37¼°W, 37.12 feet. Record: S37°W, 36.6 feet to lower face.
- White Oak, now 9-inch diameter, bears N86½°W, 20.9 feet. Record: N86¼°W, 20.6 feet to lower face.

Corner lies in an opening, under a North-South wire fence, on a 25%, N50°E, slope.

December 10, 1987
D. Edwards, Tech.

Edward McGinty
County Surveyor

V = 17¾°
P. -442