

**FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 33 ONLY  
GCDB 340100**

South Quarter corner Section 33, Township 38, Range 1 West, W.M.  $V = 20^\circ$

Found original SW BT, now a 16-inch diameter Madrone with old axe marks and reverse scribed "B." Set corner and record bearing and distance from subject tree,  $S78^\circ W$ , 15.84 feet.

N.E. BT, now a 21-inch diameter Madrone with old axe marks bears  $N81^\circ E$ , 33.0 feet. Record:  $N70^\circ E$ , 33.0 feet.

At this location I set a 1-inch x 36-inch G.I. Pipe 29 inches in the ground with 2½-inch bronze disc marked:

T38S R1W  
¼ S33  
—1973  
C.S.  
T39S R1W

From which:

- A Black Oak, 6-inch diameter, bears  $N16^\circ E$ , 20.1 feet to center of tree at lower blaze, marked CS-BT.
- A Douglas Fir, 9-inch diameter, bears  $S55\frac{1}{2}^\circ W$ , 19.5 feet to center of tree at lower blaze, marked CS- BT.

March 27, 1973  
Bob Malotte  
Rob Frost

Approved by:  
Edward McGinty,  
County Surveyor