

## FIRST RE-ESTABLISHMENT

### GCDB 400100

Section corner common to Sections 33 and 34, Township 38 South, Range 1 West, and Sections 3 and 4, Township 39 South, Range 1 West, W.M.

At the corner, found projecting 7 inches, the 1-inch diameter iron pipe set on Survey No. 1588 in 1960.

In the top of said pipe, in cement, set a 2½-inch diameter brass cap marked:

T38S R1W	
33	34
-----	
4	3
T39S	
C.S.	
1981	

From which, original bearing trees recorded by Ives and Hyde in 1854, found:

- Fir stump, 48-inch diameter, containing scribed "B" bears N50°E, 12.50 feet to scribed lower face. Record: N47°E, 12.54 feet.
- Black Oak stump, 18-inch diameter, containing reverse impression of scribed "T", bears N30°W, 3.60 feet to (reverse) scribed lower face. Record: N38°W, 3.96 feet.

Bearing trees recorded on Survey No. 1588 found with healed blazes and Re-measured to center of trees at lower blaze:

- Douglas Fir, 13-inch diameter, bears N86°10'E, 56.50 feet. Record: N86°E, 56.2 feet.
- Douglas Fir, 13-inch diameter, bears S69°30'E, 46.15 feet. Record: 45.8 feet.
- Black Oak, 13-inch diameter bears S7°W, 34.96 feet. Record: 35.5 feet.
- A found bearing tree, not of record, a Laurel 16-inch diameter, bark scribed "S33 BT" bears N81°30'W, 45.00 feet to center of tree at base.

Mark a new tree "CS" "BT":

- Black Oak, 6-inch diameter, bears N59°55'W, 26.05 feet, to center of tree at lower blaze.

Corner lies about 120 feet West of location marker on 4-inch diameter Fir in middle of old skid road, C. S65°W.

October 25, 1981  
R. Frost  
R. Templin

Edward McGinty  
County Surveyor

V = 21°  
P.-173