

## PROPORTIONED CORNER

GCDB 440700

Quarter corner common to Sections 34, Township 37 South Range 1 West and 3, Township 38 South Range 1 West, W.M.

The corner was set under GLO contract to Ives and Hyde in 1854. It was reported as destroyed by Sewall Truax during the course of Donation Land Claim survey under contract dated 1855 of the Jorasney Crawford Donation Land Claim, T38S R1W claim 84 and T37S R1W claim 53. Despite this information a proportionate search location was computed and evidence was thoroughly searched for and not found.

Set at a proportionate position between existent section corners east and west, set a 2 ins. diam. flanged GIP, with a 3 ins. diam. brass cap, 6 ins. below ground and mkd:

Jackson County Surveyor  
T37S R1W  
 $\frac{1}{4}$  S34  
S3  
T38S  
2008

From which set  $\frac{5}{8}$ -ins. diam. by 24 ins. long rebar with 1  $\frac{1}{2}$  ins. diam. aluminum caps flush with the ground and mkd:

- S28°20'57"W, 16.21 ft.
- N17°58'40"E, 20.11 ft.
- S54°26'37"E, 44.04 ft.



Section corner common to sections 35, 34, 2, 3; T37S and T38S R1W per the First Re-establishment dated 1981 brs: N89°47'42"E, 2631.44 ft.

Corner lies in SE corner of pasture.

NAD 83 (1991) Search Position Only: Northing 240117.6, Easting 4297349.3 ft.

August 20, 2008  
S.Fein  
S. Beecher

Roger Roberts  
County Surveyor

See Job File 2008-08  
Field Book Series II Book I  
P. - 33