

FIRST RE-ESTABLISHMENT

GCDB 500500

Section corner common to Sections 10, 11, 14 and 15, Township 38 South, Range 1 West, W.M.

From the following original evidence, at the location described below, set a 1x36-inch Galvanized iron pipe, 29 inches in the ground, in a small ring of stone.

In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T38S	R1W
10	11
15	14
C.S.	
1986	

Original bearing trees marked by Ives and Hyde in 1854 found:

- White Oak, now a 25-inch diameter "bee tree", with partial lower face exposed but lacking scribe marks bears N26¾°E, (Record: N26°E) Record: 26.40 feet.
- White Oak, now 12-inch diameter with scribe marks including "T38SR1W" in opened upper face, bears Record: N49°W, 29.70 feet to said face.
- A ¾-inch diameter iron pipe, set on Survey No. 1168 and found 1 inch deep, bears N88°E, 1.19 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Oak, 10-inch diameter, bears N50½°E, 65.85 feet.
- Black Oak, 18-inch diameter, bears S21°E, 67.00 feet.
- White Oak, 13-inch diameter, bears S15½°W, 42.36 feet.
- White Oak, 6-inch diameter, bears N41°W, 75.75 feet.

Corner lies in a opening, 45 feet North of the top of a rounded ridge, course S50°W, an estimated 150 feet West of a North-South wire fence.

October 31, 1986
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 17°
P. -299

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500500

Section corner common to Sections 10, 11, 14 and 15, Township 38 South, Range 1 West, W.M.

Found 1 in. galvanized iron pipe with brass cap marked

T38S	R1W
10	11
15	14
C.S.	
1986	

Protruding 6 ins. above ground surface.

Original bearing trees marked by Ives and Hyde in 1854 and noted on the First Re-establishment , dated 1986, are now gone.

Bearing trees marked on the First re-establishment found;

- White Oak 10 ins. diam., dead and down with 'CS BT' scribe visible on partially healed blazes, brs. record N50°30'E, 65.85 ft. to center of root hole.
- White Oak 14 ins. diam. with healed blazes, brs. record S15°30'W, 42.36 ft. to center of tree at lower blaze.
- White Oak 9 ins. diam. with healed blazes, brs. record N41°W, 75.75 ft. to center of tree at lower blaze.
- ¾ in. diam. iron pipe, set on Filed Survey No.1168, 1 in. deep, brs. record N88°E, 1.19 ft.

Set 1x30 ins. flanged galvanized iron pipes with 2½ ins.diam. brass caps for Reference Monuments;

1. Marked; T38S R1W , protruding 1 in. above ground surface and located 2 ft. East of North-South fence line, brs. N60°51'18"E, 169.33 ft.
RM 1 ●
2008
2. Marked; T38S R1W , protruding 3 ins. above ground surface and located 2 ft. East of North-South fence line, S76°21'42"E, 151.94 ft.
RM 2 ●
2008

Corner is located on top of East-West bearing spur ridge approx. 20 0ft. West of dirt road.

September 11, 2008
S. Beecher
S. Fein

Roger Roberts
County Surveyor

P.- 27
Series II Book I