

**SPECIAL CORNER**

**FIRST RE-ESTABLISHMENT**

**GCDB 500600**

Section corner common to Sections 2, 3, 10 and 11, Township 38 South, Range 1 West, W.M.

Found 7 inches deep, a 10 x 12 x 14-inch stone, marked with cross on top, origin unknown.

To perpetuate this position, replace said stone with and deposit it alongside a 1 x 36-inch Galvanized iron pipe, set 4 inches deep, with yellow plastic cap marked "Jackson C.S."

**Note:** Found stone was accepted as subject section corner on Survey No. 3660, dated 1968.

Take references as follows:

- Set 5/8 x 24-inch rebar, flush, with yellow plastic cap marked "Jackson C.S.", in the middle of gateway in East-West fence line, bears S20°55'W, 35.35 feet.
- Chiseled an "X" atop the Northeast corner of a 4 feet square, by 17 inches high, concrete irrigation box (most easterly of two boxes) bears S83°46'W, 16.32 feet.
- Power Pole No. D-12826 bears S89°30'W, 70.95 feet.

Corner lies on East-West fence line, 21 feet North of the middle of dust-oiled gravel road c. East-West.

May 12, 1986  
R. Frost  
T. Newcomb

Edward McGinty  
County Surveyor

P.-112

**ADDENDUM:**

Set a 2½-inch diameter brass cap in the top of 1-inch diameter pipe marked:

T38S R1W	
3	2
-----	
10	11
CS	
1994	

July 14, 1994  
T. Newcomb, Tech.  
J. Burgess, Tech.

**Note:** Above-mentioned stone referred to on Survey No. 5011 as control station "STONE."