

FIRST RE-ESTABLISHMENT
GCDB 500640

Quarter corner common to Sections 2 and 3, Township 38 South, Range 1 West, W.M.

Found the stump of the Black Oak bearing tree in Section 3 and set ½" gas pipe for corner.

From which:

- The old BT stump bears S23°W, 23.1 feet.
- A 16" Black Oak scribed ¼ SCS and BT bears N76°E, 79.0 feet.
- A 12" White Oak scribed ¼ SCS and BT bears N24°W, 156.9 feet.

April 2, 1914
A.T. Brown,
Deputy County Surveyor

H. Ling, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500640

Quarter Section corner common to Sections 3 and 2, Township 38 South, Range 1 West, W.M.

Found the ½" pipe for corner, also the Northeast BT which is now a 24" Black Oak with scribe intact, the face of which tree bears N76°E, 78.3 feet, a new BT an 18" White Oak scribed CS-BT bears N69½°W, 121.0 feet.

February 2, 1954

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 38 South, Range 1 West, W.M.

Found the ½" galvanized iron pipe exposed 10" as set for corner on the First re-establishment by Deputy County Surveyor, A.T. Brown on April 2, 1914.

Set a 1" x 36" galvanized iron pipe exposed 11" concentrically around the ½" pipe, with 2½" bronze cap stamped:

T38S R1W
¼ 3 | 2 Cor.
C.S.
1971

For corner.

From which:

- The First re-establishment bearing tree (now a 28" Black Oak, the Westerly tree in a 64" Black Oak stool, with healed faces), bears N75°59'E, 79.2 feet to center of the tree (Record: N76°E, 79.0 feet.)
- Deputy County Surveyor C. Z. Boyden's 1954 bearing tree (now a 19" White Oak, bears N69°45'W, 121.4 feet to center of the tree (1954 Record: N69½°W, 121.0 feet.)

Marked a new tree as follows:

- A 12" White Oak scribed "CS-BT" bears N59°51'E, 158.4 feet to face of the lower blaze.

January 11, 1972
Gary Kaiser,
Deputy County Surveyor

Lloyd Shreeve

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 38 South, Range 1 West, W.M.

At the corner, found projecting 6 inches, the 1-inch diameter galvanized iron pipe, with 2½-inch diameter brass cap marked:

T38S R1W
¼ 3 | 2 Cor.
C.S.
1971

Recorded on Third re-establishment dated 1972.

Bearing trees noted in 1972 found:

- White Oak, 14-inch diameter, with healed blazes, bears N59°51'E, 158.49 feet to center of tree at lower blaze. Record: 158.4 feet.
- The most Westerly branch, 33-inch diameter of a double Black Oak, bears N75°59'E, 78.94 feet to center of said branch (3 feet aboveground). Record: 79.2 feet.

Set a new reference:

- ⅝ x 24-inch rebar with yellow plastic cap marked: "Jackson County C.S." flush, 0.6 feet North of East-West fence, bears S88°44'W, 16.06 feet.
- The staff of beacon light atop the South end of the Rogue Valley Manor bears N68°12'45"W.

Corner lies 81.00 feet, S87°33'W, of Power Pole No. 12/24, 11 feet South of the middle of gravel road C. East-West and 0.6 feet North of East-West fence line.

July 16, 1984
R. Frost
E. McGinty

Edward McGinty
County Surveyor

P. -89

SEE NEXT PAGE FOR FIFTH RE-ESTABLISHMENT

FIFTH RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 38 South, Range 1 West, W.M.

Found the 1-inch galvanized iron pipe with 2½-inch diameter brass cap marked:

T38S R1W
¼ 3 | 2 COR
C S
1971

Protruding 6 inches aboveground as recorded on the Fourth Re-establishment, dated 1984.

From which:

Bearing tree marked on the First re-establishment, dated 1914, found and re-measured to the center of branch 3 feet aboveground on the Fourth Re-establishment:

- Black Oak 33-inch diameter the most westerly branch with healed blazes, bears N79°59'E, 78.52 feet. Fourth Re-establishment Record: N79°59'E, 78.94 feet.

Bearing tree marked on the Third re-establishment, dated 1972, found and re-measured on the Fourth re-establishment:

- White Oak, 15-inch diameter, with healed blazes brs, N59°54'E, 158.47 feet. Fourth Re-establishment Record: N59°54'E, 158.49 feet.

Reference set on the Fourth re-establishment found:

- ⅝-inch rebar with yellow plastic cap marked "JACKSON C.S." protruding 3 inches above ground bears Record: S88°44'W, 16.06 feet.

Take a new reference:

- A found ⅝ inch rebar, with center punch, flush with ground bears N36°15'W, 35.25 feet.

Corner lies on East-West fence line 11 feet South of the center line of gravel road along power line course East.

November 13, 1989
S. Beecher, Tech.
T. Newcomb, Tech.

Verlyn Thomas
County Surveyor

P. -226

Note: Black Oak, 33", cut down by land owner.

New Reference:

- Power Pole No. 12/24, bears N87°28'E, 81.06 feet to center.

T. Newcomb
H. Durkee
9-18-91