


FIRST RE-ESTABLISHMENT

GCDB 600100

Section corner common to Sections 35 and 36, Township 38 South, Range 1 West, and Sections 1 and 2, Township 39 South, Range 1 West, W.M.

From the following original evidence at the location described below, set at the corner, 1 x 36-inch Galvanized iron pipe, 30 inches in the ground with a 2½-inch diameter bronze cap marked:



Original bearing trees recorded by Ives and Hyde in 1854, found:

- Stump hole containing Pine fragments bears Record: S62°E, 71.94 feet.
- Stump hole and base of down Black Oak, 16-inch diameter containing reverse impression of scribed "RT" and "BT" bears Record: S23°W, 42.90 feet to estimated original position of (reverse) scribed faces.
- Laurel clump found at record location of original Northwest BT.

Mounded stones around corner, marked new trees "CS" "BT," and took measurements to center of trees at lower blaze:

- White Oak, 7-inch diameter N70°30'E, 37.00 feet.
- White Oak, 6-inch diameter S33°30'E, 9.00 feet.
- White Oak, 6-inch diameter S52°30'W, 16.28 feet.
- White Oak, 7-inch diameter N37°W, 13.20 feet.

Corner lies on Northwest slope, about 50 feet North of top of ridge, c. E-W and approximately S6°E, 500 feet from location marker on 6-inch diameter White Oak located at top of road cut bank near Southerly edge of shale pit.

October 24, 1981

R. Frost

R. Templin

Witness: G. Kaiser ORLS 803

Edward McGinty

County Surveyor

V = 19°

P.-172