

FIRST RE-ESTABLISHMENT

GCDB 600140

Quarter corner common to Sections 35 and 36, Township 38 South, Range 1 West, W.M.

Found the single remaining original bearing tree marked by Ives and Hyde in 1854.

From which evidence:

At the corner set a 1 x 36-inch Galvanized iron pipe, 30 inches in the ground with 2½-inch diameter bronze cap marked:

JACKSON COUNTY 1981
T38S R1W
¼S
35 | 36

From which:

- The root hole of a down and rotted Pine scribed "¼S" and "BT" in exposed face, bears (1854) Record: S70°E 28.38 feet to estimated original position of scribed face.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Douglas Fir, 6-inch diameter, bears N62°15'E 22.70 feet.
- Douglas Fir, 13-inch diameter, bears S87°30'W 34.72 feet.

Corner lies on North slope, 3 feet West of North-South fence line, approximately 400 feet North of location marker on 8-inch diameter White Oak located at top of ridge near 4-way road junction.

October 24, 1981

R. Frost

R. Templin

Witness: G. Kaiser (ORLS 803)

Edward McGinty

County Surveyor

V = 20°

P.-172

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600140

Quarter corner common to Sections 35 and 36, Township 38 South, Range 1 West, W.M.

Found projecting 6 inches, the 1-inch diameter galvanized iron pipe, with a 2½-inch diameter brass cap, as set on First Re-establishment dated 1981 marked:

JACKSON COUNTY 1981

T38S R1W

¼ S

35 | 36

Single remaining bearing tree marked in 1981 a Douglas Fir snag 15-inch diameter with healed blazes, bears Record: S87½°W, 34.72 feet to the center of tree at lower blaze.

Note: Found NE bearing tree down and rotted, but no visible stump hole.

Marked new trees "CS" "BT" and took measurements to the center of tree at lower blaze:

- Douglas Fir, 8-inch diameter, bears S81½°E, 18.20 feet.
- Douglas Fir, 7-inch diameter, bears N45°E, 27.59 feet.
- White Oak, 7-inch diameter, bears N34½°W, 43.93 feet.
- Madrone, 6-inch diameter, bears S35½°W, 17.85 feet.

Corner lies approximately 400 feet north of location tag on a 10-inch diameter white oak.

January 6, 1997
T. Newcomb, Tech.
C. Charlton

Roger Roberts
County Surveyor

V = 20°
P. -1