

FIRST RE-ESTABLISHMENT

GCDB 600500

Section corner common to sections 11, 12, 13, 14, Township 38 South Range 1 West, W.M.

At position set a 1 ins. diam. by 30 ins. flanged GIP with a 2 ½ ins. diam. brass cap mkd:

Jackson County Surveyor
 T38S R1W

S11	S12
S14	S13

 2008

References:

- 5/8-ins diam. by 24 ins. rebar with 1½ ins. diam. aluminum caps mkd: Jackson County Surveyor
 - ▶ Brs: N37°22'08"W, 278.81 ft., set at base of 1 ft. diam. by 6 ft. tall wood fence post.
 - ▶ Brs: N30°28'42"E, 250.55 ft., set 4 ft. west of 5 ft. tall railroad post and 4 ft. north of gravel road.
- Mag nail and washer, Brs: S13°58'38"W, 357.02 ft., set on edge of asphalt on south side of Hughes Rd.
- SE corner of DLC 81, per the third re-establishment, dated 1988 Brs: N89°48'27"W, 882.18 ft.

Corner lies in the middle of a flood irrigated pasture approx. 500 ft. north of Hughes Rd.

Job File: 2008-10

October 14, 2008

S. Fein
S. Beecher

Roger Roberts
County Surveyor

Field book Series II,
Book I, P. -42