


FIRST RE-ESTABLISHMENT

GCDB 600700

Section corner common to Sections 35 and 36, Township 37 South, Range 1 West, and Sections 1 and 2, Township 38 South, Range 1 West, W.M.

Found a large laurel stump with BT scribe visible. No other evidence of the original bearing trees could be found.

Set a 1" x 36" galvanized iron pipe with 2½" bronze cap for corner, set 34" in the ground with the cap stamped:



From which, said Laurel stump bears N17°E, 74.6 feet to the scribed face.

From said pipe corner, I establish the following new bearing trees:

- An 18" White Oak scribed "CS-BT", bears N18°W, 35.0 feet to face of blaze.
- A 30" Black Oak scribed "CS-BT", bears N4°E, 242.3 feet to the face of the upper blaze.
- A 12" White Oak, scribed "CS-BT", bears S85¼°W, 379.5 feet to face of upper blaze.

Var. 20° East
 September 8, 1965
 Lee D. Pinkham,
 Deputy County Surveyor

Lloyd W. Hart


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600700

Corner to Sections 35 and 36, Township 37 South, Range 1 West and Sections 1 and 2, Township 38 South, Range 1 West, W.M.

Found the 1" x 36" galvanized iron pipe with 2½" bronze cap stamped:



As set for corner on the First re-establishment on September 8, 1965.

Poured a concrete monument around the pipe exposed 3" and flush with the cap.

From which:

- A 20" White Oak with scribe "CS-BT" visible on a single blaze, bears N17°49'W, 34.96 feet to the face (1965 Record: 18" White Oak, N18°W, 35.0 feet to face)
- A 32" Black Oak scribed "CS-BT" bears N3°57'E, 242.4 feet to upper face (1965 Record: 30" Black Oak, N4°E, 242.3 feet to upper face.
- A 15" White Oak with scribe visible bears S85°10'W, 379.5 feet to upper face (1965 Record: 12" White Oak, S85¼°W, 379.5 feet to upper face.
- Found a 5/8" iron pin which bears S29°59'E, 19.35 feet.
- Set a 5/8" x 30" iron pin which bears S34°36'W, 316.18 feet.

March 29, 1972
Lloyd Shreeve
Ray Webber

Approved by: Mark E. Boyden
County Surveyor

SEE NEXT PAGE THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 600700

Section corner common to Sections 35 and 36, Township 37 South, Range 1 West, and Sections 1 and 2, Township 38 South, Range 1 West, W.M. $V = 17\frac{1}{2}^\circ$

Found, near the intersection of North-South and East bearing fence lines, flush in concrete, the 2½-inch diameter brass cap marked:

T37 & 38S R1W	
SEC	COR
35	36

2	1
1965	

Set for the corner, on First re-establishment, page 51, in 1965 and recorded on Second Re-establishment, page 69, in 1972.

References to corner found as follows:

- Black Oak, 32-inch diameter, with scribe marked visible in partially exposed faces, bears as recorded in 1972; $N3^\circ57'E$, 242.4 feet to scribed upper face.
- White Oak, 13-inch diameter, with healed blazes bears, as recorded in 1972, $S85^\circ10'W$, 379.5 feet to estimated upper face. Re-measured 380.06 feet to center of tree at lower blaze.
- Tipped over White Oak snag 18-inch diameter scribed "CS BT" in single (upper) face, found at record (1972) location of Northwest bearing tree.
- A 5/8-inch diameter, iron pin, found 4 inches below the surface of the ground, bears $S29^\circ55'E$, 19.35 feet. Record (1972): $S29^\circ59'E$, 19.35 feet.
- On top of above noted iron pin I place yellow plastic cap marked: "Jackson C.S."

I set new references:

- P-K nail, in the Southwest base of power pole No. 9461, bears $S48^\circ33'E$, 3.72 feet.
- 5/8 x 30 ins. rebars, flush with the surface of the ground, with yellow plastic caps marked: "Jackson C.S." bearing:
 - ▶ $S78^\circ E$, 19.02 feet.
 - ▶ $N2^\circ55'W$, 14.65 feet.

March 11, 1980
D. Danielsen
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

GCDB 600700

Section corner common to Sections 35 and 36, Township 37 South, and Sections 1 and 2, Township 38 South, Range 1 West, W.M.

Corner monument destroyed by the installation of a new power pole, No. 3/26. Set at the corner position, flush and 3 ins. southwesterly of said new power pole, a $_$ x 24 ins. rebar with 1½ ins. diam. aluminum cap marked:

JACKSON COUNTY

SURVEYOR

Also, set a 2½ x 30 ins. flanged galvanized iron pipe with a 3½ ins. diam. brass cap, exposed 6 ins. and in a mound of stones, as a witness monument marked:

JACKSON COUNTY SURVEYOR
T37S R1W
S35 | S36
—+—
S2 | S1
WIT. T38S MON.
2003

Said monument being N 0°00'43" E, 20.00 feet of section corner and on line between section corner and southeast corner of Donation Land Claim No. 55.

Bearing trees recorded on 3rd Re-establishment in 1980, found and re-measured to center of trees at lower blaze:

- White Oak, dead and down, bears N 17°57'04" W, 35.43 feet to estimated center. Record: N 18° W, 35.0 feet to face.
- Black Oak, now 33 ins. diam. with healed blazes bears N 3°45'10" E, 242.46 feet. Record: N 4° E, 242.3 feet to face of upper blaze.
- White Oak, now 16 ins. diam. with healed blazes bears S 85°02'25" W, 380.04 feet. Record: S 85¼° W, 379.5 feet to face of upper blaze.

Set new references, 5/8 x 24 ins. rebars with 1½ ins. diam. aluminum caps marked:

JACKSON COUNTY

SURVEYOR

- N53°00'32"W, 28.88 feet.
- N88°28'35"E, 111.38 feet.

(FOURTH RE-ESTABLISHMENT CONTINUED ON NEXT PAGE)

FOURTH RE-ESTABLISHMENT (Continued)

GCDB 600100

2½ ins. diam. brass cap for southeast corner of DLC No. 55 (see Re-establishment dated 1986)
found flush bears N 0°00'43" E, 760.39 feet.

¾ in. diam. iron pin per S/N 5461, found flush bears N 0°21'28" W, 760.21 feet.

PK nail found at base on southwesterly side of old power pole No. 3/26 bears S 41°31'32" E, 3.74
feet. Record: S 48°33' E, 3.72 feet.

Witness monument lies approx. 2 feet northeasterly of northerly gate post and approx. 25 feet
northerly of north, south and east fence intersection.

September 4, 2003
H. Durkee
T. Newcomb

Roger Roberts
County Surveyor

P. -134