

FIRST RE-ESTABLISHMENT

GCDB 640500

Quarter Corner common to sections 12 and 13, Township 38 South Range 1 West, W.M.

Position accepted per survey number 4964, as best available evidence. Please refer to job file for further information.

Found at position per s/n 4964 a 5/8-ins. diam. rebar inside of a 3 ins. diam. PVC pipe flush.

On found rebar set a 1½-ins. diam. brass cap, mkd: Jackson County Surveyor.

From which the following references were taken:

- Found ½ ins. diam rebar, length unknown, verbally confirmed with H. Center, PLS to be a traverse point for his project in the area. brs: S24°44'40"E, 13.57 ft.
- Found 1 ins. diam. axle, exposed 7 inches, per s/n 4964, brs: S0°01'54"W, 648.46 ft.
- Found 5/8-ins. diam. rebar per s/n 4964 in a 3 ins. diam. PVC pipe flush. brs: N88°39'15"E, 195.42 ft.
- Found Section Corner common 12, 13, 7, 18; T38S R1W and R1E per first re-establishment dated 1987 brs: S89°49'34"E, 2642.10 ft.

Field work performed between September 2007 and September 2008.

Job File 2008-10

November 25, 2008

S. Fein
S. Beecher

Roger Roberts
County Surveyor

Field Book Series II, Book I
P. -41