

FIRST RE-ESTABLISHMENT

GCDB 640700

Quarter corner common to Section 36, Township 37 South, Range 1 West, and Section 1, Township 38 South, Range 1 West, W.M.

Set a 1" x 36" galvanized iron pipe, 30" in the ground, with a 2½" bronze cap stamped:

T37 - 38S.R.1W
36 cor.
¼S —
1
C.S.
1969

From which:

- The original bearing tree (now a 21" Black Oak with both blazes left intact) bears, N35°E, 55.2 feet to the center of the tree.
- The original bearing tree (now a 22" Black Oak, plainly scribed) bears S59°E, 48.8 feet to the face of the upper blaze.
- A 12" White Oak, scribed CS-BT bears S7½°W, 62.1 feet to the face of the lower blaze.

February 14, 1969
F. Roberts,
Deputy County Surveyor

Gary Kaiser

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640700

Quarter corner common to Section 36, Township 37 South, Range 1 West, and Section 1, Township 38 South, Range 1 West, W.M.

Found protruding 4 ins. above ground and leaning northerly the 1 ins. diam. iron pipe with 2." bronze cap marked:

T37 - 38S.R.1W

¼ 36 COR.

—
1

C.S.

1969

Set on the First re-establishment dated 1969.

Reset found monument and add marks 2011 to brass cap.

From which the original bearing tree marked by Ives and Hyde in 1854;

- Black Oak 23 ins. diam., opened lower blaze to reveal partial 'BT' scribe marks, bears N35°E, 55.2 ft. to the center of the tree. Record 54.8 ft. to scibed face .

Bearing tree marked on the First re-establishment found;

- White Oak 15 ins. diam., with healed double blazes, bears record S7°W, 62.1 ft. to estimated face, re-measure 62.5 ft. to center of tree at base.

Mark new trees 'CS BT' and measure to center of tree at base;

- White Oak 13 ins. diam. bears N48½°W, 41.3 ft.
- White Oak 12 ins. diam. bears N61°E, 62.3 ft.

Corner is located on a Northwest slope, 3 ft. North of E-W fence and 10 ft. East of fence corner to E-W and South bearing fences.

May 2, 2011

S.Beecher

S. Fein

Kerry K. Bradshaw

County Surveyor

P.- 79

Series II Book I