

## FIRST RE-ESTABLISHMENT

GCDB 700300

Corner to Sections 24 and 25, Township 38 South, Range 1 West and Sections 19 and 30, Township 38 South, Range 1 East, W.M.

Found stumps of bearing trees in Sections 25 and 30, no marks legible, but stumps correspond to field notes. Set a ½" gas pipe for corner.

From which the SE corner Claim 39, Township 38 South, Range 1 East, W.M. bears East 7.16 chains, thereby checking location of two corners. No object near for references.

August 28, 1914  
A. T. Brown,  
Deputy County Surveyor

H. L. Speck, Chainman  
H. Berian, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT**

**GCDB 700300**

Corner to Sections 24 and 25, Township 38 South, Range 1 West and Sections 19 and 30,  
Township 38 South, Range 1 East, W.M.

Found ½" iron pipe 8" below surface of ground checked North to section corner, also, East to DLC  
corner. Set ¾" iron pipe with mound of stone 3' at base.

November 8, 1923  
C. Z. Boyden,  
Deputy County Surveyor

C. Garvin, Chainman  
A. Schoenberger, Chainman

**ABOVE CORNER NOT FOUND.**

**SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT**

### THIRD RE-ESTABLISHMENT

GCDB 700300

Section corner common to Section 24 and 25, Township 38 South, Range 1 West and Section 19 and 30, Township 38 South, Range 1 East, W.M.

Found 6 inches deep, the brass cap on 1-inch diameter iron pipe, marked as recorded on Survey No. 4457, dated 1971:

	T38S	
	R1W R1E	
	24   19	
Sec.	— —	Cor.
	25   30	
	RLS 759	
	1970	

The above noted survey reports the present monument replaced a found axle (origin unknown).

Set new reference; 1 x 36-inch Galvanized iron pipe, flush, with yellow plastic cap marked: "Jackson C.S." bears S89°57'17"E, 228.29 feet.

A single communication tower with (what resembles 4 marshmallows) four white panels, near top, located an estimated 300 feet Easterly of main antenna and building complex, atop Mt. Baldy, about 4 miles distant, bears N6°31'02"E.

The (brass cap) Southeast corner of DLC #39, bears S89°57'17"E, 473.13 feet. Record (Survey No. 4457), 473.26 feet.

**Note:** No evidence of the (pipe) monuments set on previous re-establishments in 1914 and 1923. See: T38S, R1W.

Corner lies in large pasture.

May 13, 1986  
R. Frost  
T. Newcomb

Edward McGinty  
County Surveyor

P.-113

**NOTE: 11/24/1987**

ADDITIONAL references taken 11/24/87, 5/8 x 24-inch rebars with yellow plastic caps marked "Jackson C.S." bear:

- N89°57'17"W, 327.10 feet, set flush, at the east edge of blackberry patch.
- S1°50'W, 23.59 feet, set 3 inches deep, in the bottom of small irrigation ditch.

R. Frost  
S. Beecher

P.-423