

SPECIAL CORNER

FIRST RE-ESTABLISHMENT

GCDB 700500

Section corner common to Sections 12 and 13, Township 38 South, Range 1 West, and Sections 7 and 18, Township 38 South, Range 1 East, W.M.

Found 2 inches deep, under a mound of stones, the 5/8-inch diameter rebar set for the corner on Survey No. 4964.

Over the top of said rebar, set a 1x36-inch Galvanized iron pipe projecting 2 inches. In the top of said pipe, set a 2 1/2-inch diameter brass cap marked:

T38S	
R1W	R1E
12	7
-----	
13	18
C.S.	
1987	

Take references as follows:

- Black Oak, 20-inch diameter scribed "CS BT", bears N52°42'E, 222.78 feet to center of tree at lower blaze.
- White Oak, 8-inch diameter with partially healed double blazes, bears S65°56'E, 87.08 feet to center of tree at lower blaze.
- White Oak, 6-inch diameter scribed "CS BT", bears S35°26'W, 293.48 feet to center of tree at lower blaze.
- The brass cap at the one quarter corner common to Sections 13 and 18, bears S0°00'06"E, 2659.12 feet.

The approximate top of an East-West sand rock ledge bears South 442 feet, more or less.

Corner lies on a gentle south slope, on line with the remains of an East-West fence, reportedly at the position of an anchor post per survey No. 4964, an estimated 520 feet North of a gravel road, 7.2 feet North of the newer East-West fence and an estimated 100 feet West of a small draw, c. N20°E.

**Note:** See Jackson County job file 86-70 for further information.

February 26, 1987  
D. Edwards  
R. Frost

Edward McGinty  
County Surveyor

P. -48