

## FIRST RE-ESTABLISHMENT

GCDB 700600

Section corner common to Sections 1 and 12, Township 38 South, Range 1 West and Sections 6 and 7, Township 38 South, Range 1 East, W.M.

Set 1" x 36" galvanized iron pipe 34" in the ground with 2½" bronze cap stamped:

T38S R1E - 1W	
1	6
12	7
C.S.	
1969	

From which:

- The original bearing tree (now a 10" Black Oak with both blazes left intact) bears N81°E, 41.8 feet to the center of the tree.
- The original bearing tree (now a 20" Black Oak snag with "BT" scribe) bears S36°E, 62.0 feet to the face of the lower blaze.
- The original bearing tree (now an 11" Black Oak snag, plainly scribed) bears S44½°W, 78.4 feet to the center of the tree.
- A 7" White Oak scribed "CS-BT" bears S27½°E, 23.1 feet to the face of the lower blaze.
- A 5" White Oak scribed "CS-BT" bears N69½°E, 8.3 feet to the face of the lower blaze.
- A 7" White Oak scribed "CS-BT" bears N29¾°W, 9.1 feet to the face of the upper blaze.
- An 8" White Oak scribed "CS-BT" bears S24¼°W, 59.6 feet to the face of the lower blaze.

February 17, 1969  
F. Roberts,  
Deputy County Surveyor

Gary Kaiser