

## FIRST RE-ESTABLISHMENT

GCDB 700640

Quarter corner common to Section 1, Township 38 South, Range 1 West and Section 6, Township 38 South, Range 1 East.

Set 1" x 36" galvanized iron pipe 32" in the ground with a 2½" bronzed cap stamped:

T38S R1W, 1E  
¼ 1 | 6 Cor.  
C.S.  
1969

From which:

- The original bearing tree, (now a 33" Black Oak, plainly scribed) bears S85°W, 368.9 feet to the face of the upper blaze.

From said pipe corner, I establish a new bearing tree as follows:

- A 5" Black Oak, scribed "CS-BT", bears S¾°W, 82.4 feet to the face of the upper blaze.

August 12, 1969  
G. Kaiser  
G. Pinkham

Approved by:  
M. E. Boyden,  
County Surveyor


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700640

Quarter corner common to Section 1, Township 38 South, Range 1 West and Section 6, Township 38 South, Range 1 East.

Found leaning severely southwesterly apparently due to unstable clay soil conditions on a southwesterly facing slope, a 1 x 36 inches galvanized iron pipe with brass cap, set per First Re-establishment dated 1969. Removed said monument and set 1 x 80 inches galvanized iron pipe driven into clay soil with top 18 inches set in concrete with a 2 ½ inch diam. brass cap exposed 6 inches, mkd.;



Bearing trees found or marked per First Re-establishment, found and measured as follows:

- Black Oak, now 42 ins. diam., with exposed original face and scribing with nail, bears S84°40'50"W, 368.90 feet to the face of the upper blaze. Record: S85°W.
- Black Oak, now 10 ins. diam. with healed upper blaze, bears S00°44'31"W, 82.61 feet to center of tree at upper blaze. Record: S¾°W, 82.40 feet to face of upper blaze.

Set new references, 5/8 x 24 ins. rebar with 2 ins. diam. aluminum cap marked "Jackson County Surveyor" :

- flush, bears N34°30'40"E, 93.09 feet.
- flush, bears S45°31'14"E, 85.53 feet.
- flush, bears S40°44'05"W, 51.80 feet.
- flush, bears N28°29'37"W, 69.05 feet.

The First Re-establishment, dated 1969, brass capped northeast section corner of Section 1, T38S R1W, W.M., bears N00°19'40"W, 2652.14 feet.

The First Re-establishment, dated 1969, brass capped southeast section corner of Section 1, T38S R1W, W.M., bears S00°21'07"E, 2655.24 feet.

Basis of Bearing: NAD 83 2011 Epoch (2010) OCRS GP/ASH zone per OAR 734-005-00015

January 3, 2019

Scott Fein

O. Ribanszky

County Surveyor

J. Hall