

FIRST RE-ESTABLISHMENT

DLC41ELL

GCDB 841140

North Northwest to DLC NO. 44, located in Section 9, Township 38 South, Range 1 West, W.M. (also being the "L" of DLC #41)

Found the 2x1 ¼-inch railroad (mining) rail projecting 2 inches determined as the corner on Survey No. 9966, in May of 1984.

To perpetuate this location, center punched the top of said rail and took references as follows:

- Set 5/8 x 24-inch rebar on East-West fence line, flush, with yellow plastic cap marked: "Jackson County C.S.", bears N88°55'E, 21.57 feet.
- Crabapple tree, 10-inch diameter (not scribed), bears S47°50'W, 21.3 feet to center of tree.
- Found a 5/8-inch diameter iron pin, flush, with plastic cap located at the corner of North and West bearing wooden fence, bears S88°55'W 40.59 feet.

Corner lies about 150 feet S16°E from the end of asphalt Northridge Terrace Street and 0.55 feet N75°W of 3-inch diameter iron pipe projecting 4 inches being the west end of east bearing fence line.

June 6, 1984
R. Frost
B. Malotte

Edward McGinty
County Surveyor

P. -60

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT SPECIAL CORNER

DLC41ELL

GCDB 841140

Reference monument to the Northerly Northwest corner of Donation Land Claim No. 44, being also the "L" corner of Donation Land Claim No. 41, located in Section 9, Township 38 South, Range 1 West, W.M.

As access to the monumented corner is becoming obstructed and visibility from the corner is increasingly limited by property development; take a reference monument to the subject DLC corner a found 2-inch diameter brass cap punched and set as the centerline of Northridge Terrace Street on the West boundary of Lakeside Estates Mobile Home Subdivision and East boundary of Northwood Park Subdivision.

Mark monument:

R.M.
C.S.
1987

From this reference monument, the Northwest corner of Donation Land Claim No. 44, a punched mining rail described on the First Re-establishment page 88, dated June 6, 1984, bears $S15^{\circ}50'04"E$, 148.56 feet distance.

From the reference monument, found:

- A $\frac{5}{8}$ -inch diameter rebar flush with ground, with yellow plastic cap marked Jackson C.S., bears $S23^{\circ}32'08"E$, 155.41 feet distance.
- A Crabapple tree, 11-inch diameter (not scribed) bears $S08^{\circ}53'11"E$, 159.29 feet distance.
- A $\frac{5}{8}$ -inch diameter rebar flush with ground, with yellow plastic cap marked "Swain LS 759", bears $S00^{\circ}00'38"E$, 143.77 feet distance.
- A brass cap 2-inch diameter punched marking the center line at the East end of Northridge Terrace Street, bears $N88^{\circ}48'20"E$, 859.00 feet distance.
- A $\frac{5}{8}$ -inch diameter rebar flush with ground with yellow plastic cap, bears $S00^{\circ}00'E$, 29.95 feet distance.

July 1, 1987
R. Frost, Tech III
S. Beecher, Tech I

Edward McGinty
County Surveyor

P.-246