

FIRST RE-ESTABLISHMENT

DLC41NE

GCDB 841100

Northeast corner of DLC #41, Township 38 South, Range 1 West, W.M.

Found the original Black Oak bearing tree to the Southwest dead with the C 41 scribe legible from which evidence set a $\frac{3}{4}$ " x 30" iron bolt flush with the surface of the ground for corner.

From which:

- A 12" White Oak scribed CS-BT bears N12½°E, 51.2 feet.
- Scribe a forked 14" Black Oak CS-BT which bears N59½°W, 63.4 feet.
- Scribe an 8" forked White Oak CS-BT which bears S22½°E, 101.2 feet.

February 1, 1954

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC41NE

GCDB 841100

Northeast corner of Donation Land Claim No. 41, Township 38 South, Range 1 West.

The iron bolt corner monument has been destroyed.

Set a 1"x 31" galvanized iron pipe 6" below the surface of the ground for corner.

- A 12" White Oak plainly scribed bears North 13° East, 50.9 feet to the face of the upper blaze;
- An 8" forked White Oak with healed blazes bears South 22¾° East, 100.5 feet to the face of the tree at the lower blaze.
- The middle fork of a triple 9" White Oak scribed CS-BT bears North 57¼° West, 125.4 feet.

February 23, 1967

F. A. Roberts

Gerald Nygren

Approved by:

L. D. Pinkham

Deputy County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC41NE

GCDB 841100

Northeast corner to DLC NO. 41, located in Section 4, Township 38 South, Range 1 West, W.M.

At the corner, found 4 inches deep, 2½-inch diameter brass cap in concrete (not of record) marked:

T38S R1W

DLC NE

Cor. 41
C.S.
1971

The single remaining bearing tree (marked on Second Re-establishment in 1967), the Southeast branch 10-inch diameter, of a triple White Oak with healed blazes, bears N57°15'W, 125.90 feet to center of tree at lower blaze. Record: 125.4 feet.

Marked a new tree "CS" "BT":

- The Easterly branch, 14-inch diameter, of a double White Oak, bears S26°50'W, 124.40 feet to center of tree at lower blaze.

Set new references; 5/8 x 24-inch rebars, flush with yellow plastic caps marked "Jackson County C.S.", on line with the above noted extant bearing trees:

- N57°15'W, 122.47 feet.
- S26°50'W, 121.25 feet.

May 14, 1984

R. Frost

B. Malotte

Edward McGinty

County Surveyor

P. -58