

FIRST RE-ESTABLISHMENT

DLC43NE

GCDB 843100

Re-establishment NE corner of DLC #43, Township 38 South, Range 1 West.

Found the 4" x 4" x 14" red sand stone with cross on top 3" aboveground set by me in September 1927 at which time the Northwest and Southwest BTs were in good condition. Said tree are now badly decayed.

From said stone for corner:

- A 10" White Oak scribed CS-BT bears N14°W, 240.2 feet;
- 16" forked White Oak scribed CS-BT bears N48°W, 116.1 feet. (Note 2 trees in Northwest quadrant)
- 10" White Oak scribed CS-BT bears S40½°W, 79.9 feet.

December 17, 1953

C. Z. Boyden

L. D. Pinkham

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC43NE

GCDB 843100

Northeast corner to Donation Land Claim NO. 43, located in Section 14, Township 38 South, Range 1 West, W.M.

Found flush, a 3-inch diameter brass cap marked:

T38S R1W
DLC
NE Cor. 43
C.S.
1972

Embedded in a 9 inches square concrete pedestal, set on Survey No. 5011.

Bearing trees marked on First Re-establishment, page 30, in 1953 found and measured to center of trees at lower blaze:

- White Oak, now 14-inch diameter with double healed blazes, bears $S41\frac{1}{2}^{\circ}W$, 79.6 feet.
Record: $S40\frac{1}{2}^{\circ}W$, 79.9 feet.
- White Oak, now 31-inch diameter with double healed blazes, bears $N48\frac{1}{2}^{\circ}W$, 115.85 feet.
Record: $N48^{\circ}W$, 116.1 feet.
- White Oak, now 15-inch diameter, with double healed blazes, bears Record: $N14^{\circ}W$, 239.3 feet. Record distance; 240.2 feet.

Corner lies at intersection of east, west and south bearing fences, in open field, on 20% east slope, approximately 100 feet northwest of a pond.

June 18, 1987
D. Edwards, Tech II
T. Newcomb, Tech I

Edward McGinty
County Surveyor

$V = 16\frac{1}{2}^{\circ}$
P. -199