

## FIRST RE-ESTABLISHMENT

DLC46NE

GCDB 846100

Northeast corner to DLC #46, Township 38 South, Range 1 West.

Found sandstone with cross on top, the recognized corner for over 30 years.

From which:

- The center of a 26" White Oak (not scribed) bears  $S65\frac{1}{4}^{\circ}E$ , 91.0 feet.
- Set a 1" iron pin which bears North 30.0 feet.
- A 1" iron pin bears  $N72^{\circ}10'W$ , 98.2 feet.
- A  $1\frac{1}{2}$ " x 36" galvanized iron pipe, the Southeast corner DLC #50, bears  $N89^{\circ}55'W$ , 93.45 feet.

March 1941  
C. Z. Boyden  
C. I. Bourne  
A. H. Smith

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

DLC46NE

GCDB 846100

Northeast corner DLC #46, Township 38 South, Range 1 West, W.M.

Found sandstone with cross 21" below the surface of the county road as reported for corner on the First Re-establishment in March 1941.

Replaced said stone with a 20" diameter by 14" deep concrete monument with a 3" bronze disk 8" deep in a monument case stamped:

JACKSON COUNTY  
T38S R1W  
NE DLC  
Cor. 46  
1970  
CONTROL MONUMENT

From which:

- Found a 1" axle 3" deep which bears N0°16'E, 30.00 feet (1941 Record: 1" iron pin, North 30.0 feet.)
- The center of the First re-establishment bearing tree, now a 40" White Oak (not scribed), bears S65°26'E, 91.6 feet. (Record: 26" White Oak not scribed) bears S65¼°E, 91.0 feet to the center.)
- The Southeast corner of DLC NO. 50, a 1½" galvanized iron pipe, bears N89°51'W, 93.5 feet. (1941 Record: N89°55'W, 93.45 feet.)

March 28, 1972  
Lloyd Shreeve  
Ray Webber

Approved by:  
M. E. Boyden,  
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT      SPECIAL CORNER

DLC46NE  
GCDB 846100

Northeast corner to Donation Land Claim No. 46, located in Section 5, Township 38 South, Range 1 West, W.M.

Found the 3-inch diameter bronze disk described on the Second Re-establishment, page 58, dated 1972, 8 inches below the surface of pavement, in monument case.

Directly over found monument set a 2½-inch diameter brass cap marked:

T38S R1W  
NE | DLC  
46 |  
C.S.  
1988

Flush with pavement in cement, from which, references reported in 1972 found:

- 1-inch diameter axle to Northeast is bent and partially dislodged.
- White Oak, 28-inch diameter (recorded as 40-inch diameter in 1972) not scribed bears S65°26'E, 89.92 feet to center of tree at base. Record: 93.5 feet.

Take new references:

5/8 x 24-inch rebars with yellow plastic cap marked "Jackson C.S.":

- Flush 2 feet West of 6-inch diameter Black Walnut bears N11°52'30"E 29.70 feet.
- Set 1 inch deep, bears S65°24'55"E, 82.39 feet.

The brass cap Southeast corner to Donation Land Claim No. 50, bears N89°51'W, 93.42 feet. Corner lies in East bound lane of South Stage Road, at Voorhies Jct.

May 26, 1988  
S. Beecher, Tech.  
R. Frost, Tech.

Edward McGinty  
County Surveyor

P. -206

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

**FOURTH RE-ESTABLISHMENT      SPECIAL CORNER**

**DLC46NE**

**GCDB 846100**

Northeast Corner to Donation Land Claim No. 46, located in Section 5, Township 38 South, Range 1 West, W.M.

Found an unrecorded 1994 Jackson County brass cap flush with road surface. Dug underneath cap and found the brass cap set on the Second Re-establishment, dated 1970, 16 inches below road surface.

Directly over found monument set a 1-inch x12-inch galvanized iron pipe with 2½-inch diameter brass cap marked:

T38S R1W  
DLC  
NE  
46  
2000

JACKSON COUNTY SURVEYOR

In monument case.

The Southeast Corner of Donation Land Claim 50, bears N89°52'24"W, 93.43 feet. Third Re-establishment, dated 1988, bears record: N89°51'W, 93.42 feet.

All Third re-establishment references are now gone or damaged.

New references:

- Found 5/8-inch diameter rebar with aluminum cap marked 'JACKSON COUNTY Δ C.S.' protruding 2 inches, bears N63°15'35"E, 79.72 feet.
- Found 1¼-inch diameter iron pipe flush with ground, located 3 feet West of the center of Voorhies Road, bears S03°38'26"W, 81.97 feet.
- Found 5/8-inch diameter rebar with yellow plastic cap marked, 'JACKSON COUNTY ROADS & PARKS SVC.' flush with ground, bears S57°47'05"W, 95.93 feet. Located ½ foot North of fence.

Set 5/8 x 24-inch rebar with aluminum cap marked 'JACKSON COUNTY Δ C.S.' flush with ground:

- Bears S81°13'07"W, 64.47 feet. Located 10 feet North of phone box and in shoulder of road.
- Bears S17°25'00"W, 100.57 feet. Located 3 feet North of a fence line projecting South.

Corner lies in East bound lane of South Stage Road, at Voorhies Junction.

September 28, 2000

T. Newcomb

S. Beecher

City of Medford: D. Doi, B. Beeman

Roger Roberts

County Surveyor

P. -18 & 57-57A