

FIRST RE-ESTABLISHMENT

DLC46SE

GCDB 845110

Southeast corner DLC #46 (also Northerly "L" DLC #45), Township 38 South, Range 1 West.

Found 8" x 12" x 12" blue sandstone 8" below the surface of the County Road, the recognized corner. Chiseled + in top of stone for corner.

From which:

- Set a $\frac{3}{4}$ " x 23" iron bolt 8" below the surface of the ground which bears East 25.0 feet;
- Set a $\frac{3}{4}$ " x 23" iron bolt which bears West 30.0 feet.;
- The center of a 32" White Oak (now scribed) bears S38 $\frac{3}{4}$ °E, 102.9 feet.

May 14, 1940

C. Z. Boyden

C. I. Bourne

A. H. Smith

NOTE:

Chiseled X on N. end Wly concrete wall irr. diversion box which bears N75°W, 28.98 feet.

C. Z.B.

February 1, 1943

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC46SE

GCDB 845110

Southeast corner of DLC #46, Township 38 South, Range 1 West, W.M. (Also being Northerly "L" DLC #45)

Found a stone with cross 11" below the surface of the County road for corner as reported on the First Re-establishment on May 14, 1940.

Replaced said stone with a 20" diameter by 14" deep concrete monument with a 3" bronze cap 8" deep in a monument case, stamped:

JACKSON COUNTY
T38S R1W
SE DLC
Cor. 46
1970
CONTROL MONUMENT

From which:

- Found the $\frac{3}{4}$ " iron bolt 8" deep which bears S89°55'E, 25.00 feet (1940 Record: East 25.0 feet.)
- The First Re-establishment bearing tree, now a 40" White Oak, not scribed, bears S38°29'E, 102.8 feet to the center (1940 Record: 32" White Oak, S38 $\frac{3}{4}$ °E, 102.9 feet to center)

I took new reference tree as follows:

- A 16" Pear tree, not scribed, being the most Northeasterly one South of the entrance to a pear orchard, bears S55°29'W, 46.8 feet to the center.

March 28, 1972
Lloyd Shreeve
Ray Webber

Approved by:
M. E. Boyden,
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC46SE

GCDB 845110

Southeast corner to Donation Land Claim No. 46, identical with the Northerly "L" corner of Donation Land Claim No. 45, located in Section 8, Township 38 South, Range 1 West, W.M.

Found 8 inches below and near the center of Voorhies Road, in a monument case, the brass cap described on Second Re-establishment, dated 1972.

References recorded in 1972 found:

- White Oak, 34-inch diameter, (note scribed) bears S38°38'E, 102.67 feet to center of tree at base. Record: S38°29'E, 102.8 feet.
- Bolt, ¾-inch diameter found 16 inches deep, bears N89°54'E, 24.99 feet. Record: S89°55'E, 25.0 feet.

To perpetuate this location, set new reference; 5/8x30-inch rebar, flush, with yellow plastic cap marked: JACKSON County C.S. located 4 feet west of concrete lines irrigation ditch, bears S89°54'W, 30.84 feet.

- The staff of the beacon light on the South end of the Rogue Valley Manor, bears N12°19'22"E.
- The (brass cap) Northeast corner of Donation Land Claim No. 46, bears N0°09'50"E, 3197.25 feet.
- The (1-inch diameter pipe) South Southwest corner of Donation Land Claim No. 46, bears S89°54'11"W, 978.19 feet.

July 10, 1984
R. Frost
Edward McGinty

Edward McGinty
County Surveyor

P. -82

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT SPECIAL CORNER
DLC46SE
GCDB 845110

Fd. unrecorded 2½-ins. diam. brass cap flush in concrete mkd:

T38SR1W
DLC
SE |
46—°
C.S.
1996

Note: brass cap is oriented to the south.

Basis of bearing: 2½-ins. diam. cap mkd. For the NNW of DLC 45, set on first reestablishment, dated 1996, brs. N00°10'15"E, 1691.56 ft. Record 2691.55 ft.

Found unrecorded 5/8 ins. diam rebar with aluminum caps mkd. "Jackson County CS" set flush:

1. S36°09'23"E, 41.05 ft., located 1½ feet west of south end of gateway.
2. N35°32'40"W, 43.00 ft.

References fd. or set on Third Re-establishment dated 1984 fd:

1. 1¼-ins. diam. bolt head, 14 ins. deep, bears N89°50'45"E, 24.96 ft., located 1 foot west of Right-of-way fence. Record N89°54'E, 24.99 ft.
2. 5/8-ins. diam. rebar with yellow plastic cap mkd. "Jackson County CS", bears S89°56'55"W, 30.78 ft., located 1 foot west of west edge of concrete irrigation ditch. Record S89°54'W, 30.84 ft.

Corner is located near the center of Voorhies road.

October 4, 2000
T. Newcomb

Roger Roberts
County Surveyor

P. -63