

FIRST RE-ESTABLISHMENT

DLC56SSW

GCDB 856130

Re-establishment South, Southwest corner DLC #56, Township 38 South, Range 1 West (abandoned).

Found the 1½" galvanized pipe set for corner by myself in 1937. Now all that remains of the original BTs is an oak stump to Northeast, Oak roots to Northwest and Oak stump to Southeast.

From the 1½" pipe, 8" aboveground for corner an 8" White Oak scribed CS-BT bears N76¾°E, 63.8 feet:

- A 7" White Oak scribed CS-BT bears N71°W, 31.7 feet;
- A 1½" galvanized pipe at the Northwest corner of DLC #57 bears East 210.7 feet.

December 18, 1953

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC56SSW

GCDB 856130

South Southwest corner to DLC No. 56 (abandoned), located in Section 21, Township 38 South, Range 1 West, W.M.

At the corner, found projecting 5 inches, the 1½-inch diameter iron pipe, reported on First Re-establishment in 1953.

In the top of said pipe, in cement, set a 2½-inch diameter brass cap marked:

T38S R1W
DLC
SSW
56
C.S.
1985

The single remaining bearing tree marked in 1953,

- A White Oak, now 9-inch diameter, with healed blazes, bears N71°W, 31.98 feet to center of tree at lower blaze. Record: 31.7 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Oak, 7-inch diameter, bears N25°30'E, 45.55 feet.
- White Oak, 6-inch diameter, bears S34°W, 28.60 feet.

Corner lies about 210 feet West of the Northwest corner of DLC No. 57, approximately 85 feet West of irrigation canal and 2 feet South of East-West fence line.

January 17, 1985
E. McGinty
R. Frost

Edward McGinty
County Surveyor

V = 20½°
P. -22

NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC56SSW

GCDB 856130

SSW corner of Donation Land Claim No. 56, located in Section 21, Township 38 South, Range 1 West, W.M.

Found at the corner position, atop a 1½-inch diameter galvanized iron pipe and exposed 5 inches the 2½-inch diameter brass cap set on Second Re-establishment in 1985, marked:

T38S R1W
DLC
SSW
56
C.S.
1985

- Single remaining bearing tree recorded on First Re-establishment in 1953, a White Oak, now 10-inch diameter with healed blazes, bears Record: N 71° W, 31.98 feet to center of tree at lower blaze.
- Both White Oak bearing trees marked on Second Re-establishment were present, but not re-measured.

New references taken:

- 5/8 x 30-inch rebar with 1½-inch diameter aluminum cap marked:

JACKSON COUNTY

SURVEYOR

bears: N61°19'06" E, 21.66 feet.

NW corner of Donation Land Claim No. 57 bears: S 89°54'20" E, 211.08 feet.

Corner lies approximately 85 feet west of irrigation canal and 2 feet south of east-west fence line.

May 15, 2003

H. Durkee

T. Newcomb

Roger R. Roberts

Jackson County Surveyor

P. - 81