

FIRST RE-ESTABLISHMENT

DLC57SW

GCDB 857110

Southwest corner of DLC #57, Township 38 South, Range 1 West, W.M.

- Found one witness tree intact, a 20" White Oak which bears S39°E, 74 lks.
- Also found stumps of two trees in proper location for other witness trees.

Set stake scribed C 57 T38S R1W and ½" iron pipe and two witness trees as follows:

- A 10" Laurel bears S69½°W, 31.9 feet, scribed C 57 S 28 T38S R1W on upper blaze and BT on lower blaze.
- A 24" White Oak bears N50°E, 64.0 feet scribed C 57 on upper blaze and BT on lower.

March 19, 1914
A. T. Brown,
Deputy County Surveyor

H. Ling, Chainman
P. Murphy, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC57SW

GCDB 857110

Southwest corner of DLC #57, Township 38 South, Range 1 West, W.M.

- Found a portion of the old wood stake and the ½" pipe set for corner.
- Also found the Northeast BT intact, the stump of the Laurel to the Southwest, all of which were established by County Surveyor A.T. Brown in the year 1914.
- Also found the remains of the original Southeast BT.

At the exact location of the said ½" iron pipe corner set a 1 5/8" x 36" steel tube 36" in the ground for corner.

From which:

- The 24" White Oak with scribe legible bears N50½°E, 63.0 feet.
- Scribe a 6" White Oak CS-BT which bears N6½°E, 86.8 feet.
- An old mining prospect hole bears N63°W, 66.0 feet.
- Scribe a 12" White Oak CS-BT which bears S18½°W, 61.9 feet.

November 19, 1953

C. Z. Boyden

L. D. Pinkham

T. Furnas

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC57SW

GCDB 857110

The Southwest corner to DLC #57, Township 38 South, Range 1 West, W.M.

At the corner, found flush with the ground, in concrete a (unrecorded) 3-inch diameter brass cap marked:

T38S	R1W
SW	DLC
Cor.	57

1972

Bearing tree recorded on First Re-establishment in 1914, found:

- White Oak, 22-inch diameter, with healed blazes, bears Record: N50½°E, 63.0 feet to estimated face. Re-measured; 64.0 feet to center of tree.

Bearing trees marked on Second Re-establishment in 1953 found:

- The base and root hole of a tipped over White Oak, 7-inch diameter bears Record: N6½°E, 86.8 feet.
- The base of a down and rotted Oak, 12-inch diameter, bears Record: S18½°W, 61.9 feet.

Add the marks "1983" to found brass cap and set new references: 5/8 x 30-inch rebars, flush, with yellow plastic cap marked "JACKSON C.S." br.:

- N17°43'E, 89.75 feet, located on fence line c. N30°W, and about 24 feet Westerly of the center of 12 feet diameter concrete foundation for satellite (TV) reception antenna.
- S17°25'W, 17.40 feet, located 3 feet Easterly of the center of 12-inch diameter Madrone.

The Northwest corner of wood, frame house, (residence 6766 Adams Rd) bears N76°02'E, 104.50 feet.

May 5, 1983
R. Frost
R. Templin

Edward McGinty
County Surveyor

V = 18°
P.-43