

FIRST RE-ESTABLISHMENT

DLC60NNW

GCDB 860110

Most Northerly Northwest corner DLC #60 on East Boundary of DLC #59, Township 38 South, Range 1 West, W.M.

Found stump of original yellow pine BT to Northeast from which set:

- A 1½" x 36" galvanized pipe, 36" in the ground per corner.

From which:

- A 12" Black Oak scribed CS-BT bears N75°15'E, 21.3 feet.
- A 10" Black Oak scribed CS-BT bears N05°30'W, 21.1 feet.
- A 5" Ash scribed CS-BT bears S86°30'W, 25.9 feet.

July 11, 1930
C. Z. Boyden,
Deputy County Surveyor
Tice & Pettegrew, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
DLC60NNW – WITNESS CORNER
GCDB 860110**

Establishment of a witness corner for the most-Northerly Northwest corner of DLC #60, Township 38 South, Range 1 West.

Found the pipe corner monument, the Northeast Black Oak witness tree plainly scribed and the stump of the Northwest Black Oak witness tree, all of which were reported in the First Re-establishment by C. Z. Boyden on July 11, 1930.

Because the recent Bear Creek flood erosion may destroy said corner, I establish a witness corner 105.70 feet Easterly on the North line of said claim where I set a 1"x36" galvanized iron pipe for witness corner.

From which:

- A 10"x 16" forked white oak, scribed WC-CS-BT bears N70½°E, 5.3 feet to the lower blaze;
- A 22" White oak scribed WC CS-BT bears N42½°W, 35.4 feet.

February 25, 1956
Mark E. Boyden
C. Z. Boyden

SEE NEXT PAGE FOR NEXT RE-ESTABLISHMENT

**THIRD RE-ESTABLISHMENT
DLC60NNW – WITNESS CORNER
GCDB 860110**

Witness corner to North Northwest corner DLC No. 60, Township 38 South, Range 1 West, located in Section 22, W.M. $V = 20^\circ$

Found, 1 x 36 inch G.I. pipe 6 inches below ground surface as established for witness corner by M. E. Boyden in 1956.

I replace with a 1 x 36-inch G.I. pipe and 2½-inch diameter with bronze disc marked:

JACKSON COUNTY 1979
T38S R1W
W.C.
NNW
DLC
60

I drive said pipe 3 inches deep.

From which I find a forked (2) White Oak, unblazed fork is 12-inch diameter and blazed fork is 17-inch diameter with visible scribe, "CCS" in upper blaze, bears $N76^\circ E$, 5.86 feet to 8d nail on Northwest side of tree. Record $N70\frac{1}{2}^\circ E$, 5.3 feet.

I Mark the following references:

- A concrete nail and shiner at top of 8 inches concrete wire wing wall bears $S29^\circ W$, 22.95 feet.
- Black Oak, 5-inch diameter scribed "CS" in upper blaze only, bears $N29^\circ W$, 12.88 feet to center of tree at base.
- I deposit pipe alongside, mound stone around and drive a 6 feet steel fence post 9 inches North of corner.

Corner lies South of road course - $N80^\circ W$, at bottom of side slope.

July 10, 1979
J. Swanson
J. Gallegos

Approved by: Edward McGinty
County Surveyor